



Mounting	Recessed
Wattage	8W
Voltage	DC24V
Dimensions	(D) Ø135mm x (H) 125mm
Cut Out Dimensions	(D) Ø125mm
Finish	Stainless Steel
CCT	3000K, 4000K
Beam Angle	10°, 15°, 20°, 30°
Material	Stainless Steel 316 & Aluminium Body
IP Rating	IP67
IK Rating	IK09
Luminous Flux	500lm
CRI	>92+
Accessories	Gimble Tool, Honeycomb Lense
Colour Deviation	<3 SDCM
Lifetime	50,000 hours
Control Gear	1-10V, DALI, Non-dimmable
Warranty	5 years
Luminaires Type	Outdoor

Control Gear

Accessories
Gimble Tool, Honeycomb Lense

AME.AD135						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AD135	Recessed	8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AD135	Recessed	8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AD135	Recessed	8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	1-10V	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	DALI	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	1-10V	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	DALI	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	1-10V	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	DALI	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	1-10V	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	DALI	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	1-10V	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	DALI	5 years	Outdoor
	AME.AD135 Recessed 8W	DC24V	8W	DC24V	(D) 135mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+ <3 SDCM		50,000 hours	Non-dimmable	5 years	Outdoor



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AD135 Recessed 8W		8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AD135 Recessed 8W		8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AD135 Recessed 8W		8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AD135 Recessed 8W		8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AD135 Recessed 8W		8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AD135 Recessed 8W		8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor