



<b>Mounting</b>	Recessed
<b>Wattage</b>	8W
<b>Voltage</b>	DC24V
<b>Dimensions</b>	(D) Ø135mm x (H) 125mm
<b>Cut Out Dimensions</b>	(D) Ø125mm
<b>Finish</b>	Stainless Steel
<b>CCT</b>	3000K, 4000K
<b>Beam Angle</b>	10°, 15°, 20°, 30°
<b>Material</b>	Stainless Steel 316 & Aluminium Body
<b>IP Rating</b>	IP67
<b>IK Rating</b>	IK09
<b>Luminous Flux</b>	500lm
<b>CRI</b>	>92+
<b>Accessories</b>	Gimble Tool, Honeycomb Lense, Mounting Sleeve
<b>Colour Deviation</b>	<3 SDCM
<b>Lifetime</b>	50,000 hours
<b>Control Gear</b>	1-10V, DALI, Non-dimmable
<b>Warranty</b>	5 years
<b>Luminaires Type</b>	Outdoor

Control Gear

Accessories  
Gimble Tool, Honeycomb Lense, Mounting Sleeve

AME.AU135						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

## VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AU135	Recessed	8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	1-10V
	AME.AU135	Recessed	8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	DALI
	AME.AU135	Recessed	8W	DC24V	(D) Ø135mm x (H) 125mm	(D) Ø125mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	Non-dimmable



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	1-10V
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	DALI
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	Non-dimmable
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	1-10V
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	DALI
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	Non-dimmable
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	1-10V
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	DALI
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	Non-dimmable
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	1-10V
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	DALI
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	Non-dimmable
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	1-10V
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	DALI
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	Non-dimmable



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	1-10V
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	DALI
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	Non-dimmable
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	1-10V
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	DALI
	AME.AU135	Recessed	8W	DC24V	(D) 35mm x (H) 125mm	(D) 125mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	500lm	>92+	<3 SDCM	50,000 hours	5 years	Outdoor	Non-dimmable