AME.AU185..... ADJUSTABLE UPLIGHT 185






Mounting	Recessed
Wattage	18W
Voltage	DC24V
Dimensions	(D) Ø185mm x (H) 153mm
Cut Out Dimensions	(D) Ø175mm
Finish	Stainless Steel
CCT	3000K, 4000K
Beam Angle	10°, 15°, 20°, 30°
Material	Stainless Steel 316 & Aluminium Body
IP Rating	IP67
IK Rating	IK09
Luminous Flux	1100lm
CRI	>92+
Accessories	Gimble Tool, Honeycomb Lense, Mounting Sleeve
Colour Deviation	<3 SDCM
Lifetime	50,000 hours
Control Gear	1-10V, DALI, Non-dimmable
Warranty	5 years
Luminaires Type	Outdoor
Luminous Flux lm	1001-1500lm

Control Gear

Accessories

Gimble Tool, Honeycomb Lense, Mounting Sleeve



VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU185	Recessed	18W	DC24V	(D) Ø185mm x (H) 153mm	(D) Ø175mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1100lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor