



Mounting	Recessed
Wattage	26W
Voltage	DC24V
Dimensions	(D) Ø215mm x (H) 173mm
Cut Out Dimensions	(D) Ø205mm
Finish	Stainless Steel
CCT	3000K, 4000K
Beam Angle	10°, 15°, 20°, 30°
Material	Stainless Steel 316 & Aluminium Body
IP Rating	IP67
IK Rating	IK09
Luminous Flux	1650lm
CRI	>92+
Accessories	Gimble Tool, Honeycomb Lense, Mounting Sleeve
Colour Deviation	<3 SDCM
Lifetime	50,000 hours
Control Gear	1-10V, DALI, Non-dimmable
Warranty	5 years
Luminaires Type	Outdoor
Luminous Flux lm	1501-2000lm

Control Gear

Accessories
Gimble Tool, Honeycomb Lense, Mounting Sleeve

AME.AU215						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AU215 Recessed	26W	DC24V	(D) Ø215mm x (H) 173mm	(D) Ø205mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor	
	AME.AU215 Recessed	26W	DC24V	(D) Ø215mm x (H) 173mm	(D) Ø205mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor	
	AME.AU215 Recessed	26W	DC24V	(D) Ø215mm x (H) 173mm	(D) Ø205mm	Stainless Steel	3000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor	



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	3000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	3000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	3000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	4000K	10°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	1-10V	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	DALI	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	Ø115mm x (H) 17.5mm	Ø205mm	Stainless Steel	4000K	15°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3	SDCM	50,000 hours	Non-dimmable	5 years	Outdoor



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	AME.AU215	Recessed	26W	DC24V	(D) Ø115mm x (H) 17.3mm	(D) Ø205mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3 SDCM		50,000 hours	1-10V	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	(D) Ø115mm x (H) 17.3mm	(D) Ø205mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3 SDCM		50,000 hours	DALI	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	(D) Ø115mm x (H) 17.3mm	(D) Ø205mm	Stainless Steel	4000K	20°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3 SDCM		50,000 hours	Non-dimmable	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	(D) Ø115mm x (H) 17.3mm	(D) Ø205mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3 SDCM		50,000 hours	1-10V	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	(D) Ø115mm x (H) 17.3mm	(D) Ø205mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3 SDCM		50,000 hours	DALI	5 years	Outdoor
	AME.AU215	Recessed	26W	DC24V	(D) Ø115mm x (H) 17.3mm	(D) Ø205mm	Stainless Steel	4000K	30°	Stainless Steel 316 & Aluminium Body	IP67	IK09	1650lm	>92+ <3 SDCM		50,000 hours	Non-dimmable	5 years	Outdoor