



Mounting	Plaster Recessed
Wattage	4W
Voltage	240V
Dimensions	(W) 114mm x (H) 56.5mm x (L) 70mm
Cut Out Dimensions	(W) 70mm x (L) 70mm
Finish	Black, White
Inner Trim Finish	Black
CCT	2700K, 3000K, 3500K, 4000K
Beam Angle	10°, 15°, 30°, 45°
Material	Aluminium
Driver	Remote
IP Rating	IP23
UGR	<19
Luminous Flux	310lm
CRI	>92+
Colour Deviation	<2 SDCM
Accessories	Clear Filter, Frosted Filter, Vertical Filter, Woven Filter
Lifetime	50,000 hours
Control Gear	DALI, Phase-Cut
Warranty	5 years
Luminaires Type	Recessed
Luminous Flux lm	1-500lm

Control Gear

Accessories

Clear Filter, Frosted Filter, Vertical Filter, Woven Filter

DOT.PR75						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm x (H) 56.5mm x (L) 70mm	(W) 70mm x (L) 70mm	Black	Black	2700K	10°	Aluminium	IP23	<19	310lm	>92+	2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm x (H) 56.5mm x (L) 70mm	(W) 70mm x (L) 70mm	Black	Black	2700K	15°	Aluminium	IP23	<19	310lm	>92+	2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm x (H) 56.5mm x (L) 70mm	(W) 70mm x (L) 70mm	Black	Black	2700K	30°	Aluminium	IP23	<19	310lm	>92+	2 SDCM	50,000 hours	5 years	Recessed Remote	



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	2700K	45°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	3000K	10°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	3000K	15°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	3000K	30°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	Any Cut Out Dimensions	Black	Black	3000K	45°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	3500K	10°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	3500K	15°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	3500K	30°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	3500K	45°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	4000K	10°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	4000K	15°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	4000K	30°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	Black	Black	4000K	45°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	2700K	10°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	2700K	15°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Fin Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaire Type
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	2700K	30°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	2700K	45°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	3000K	10°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	3000K	15°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	3000K	30°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	3000K	45°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	3500K	10°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	3500K	15°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	3500K	30°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	3500K	45°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	4000K	10°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	4000K	15°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	4000K	30°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
	DOT.PR75	Plaster Recessed	4W	240V	(W) 114mm (H) 84mm (L) 56.5mm x 70mm	(W) 70mm (L) 70mm	White	Black	4000K	45°	Aluminium	IP23	<19	310lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	

