



<b>Mounting</b>	<u>Recessed</u>
<b>Wattage</b>	<u>20W</u>
<b>Voltage</b>	<u>240V</u>
<b>Dimensions</b>	<u>(W) 45mm x (H) 49mm x (L) 280mm</u>
<b>Cut Out Dimensions</b>	<u>(W) 37mm x (L) 273mm</u>
<b>Finish</b>	<u>Black, White</u>
<b>Inner Trim Finish</b>	<u>Black</u>
<b>CCT</b>	<u>2700K, 3000K, 3500K, 4000K</u>
<b>Beam Angle</b>	<u>10°, 15°, 30°, 45°</u>
<b>Material</b>	<u>Aluminium</u>
<b>Driver</b>	<u>Remote</u>
<b>IP Rating</b>	<u>IP23</u>
<b>UGR</b>	<u>&lt;19</u>
<b>Luminous Flux</b>	<u>1350lm</u>
<b>CRI</b>	<u>&gt;92+</u>
<b>Colour Deviation</b>	<u>&lt;2 SDCM</u>
<b>Accessories</b>	<u>Clear Filter, Frosted Filter, Vertical Filter, Woven Filter</u>
<b>Lifetime</b>	<u>50,000 hours</u>
<b>Control Gear</b>	<u>DALI, Phase-Cut</u>
<b>Warranty</b>	<u>5 years</u>
<b>Luminaires Type</b>	<u>Recessed</u>
<b>Luminous Flux lm</b>	<u>1001-1500lm</u>

Control Gear

Accessories

Clear Filter, Frosted Filter, Vertical Filter, Woven Filter

DOT.R280							
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR	

## VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 49mm x (L) 280mm	(W) 37mm (L) 273mm	Black	Black	2700K	10°	Aluminium	IP23	<19	<19	1350lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 49mm x (L) 280mm	(W) 37mm (L) 273mm	Black	Black	2700K	15°	Aluminium	IP23	<19	<19	1350lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 49mm x (L) 280mm	(W) 37mm (L) 273mm	Black	Black	2700K	30°	Aluminium	IP23	<19	<19	1350lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed Remote



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	2700K	45°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	3000K	10°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	3000K	15°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	3000K	30°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	3000K	45°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	3500K	10°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	3500K	15°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	3500K	30°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	3500K	45°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	4000K	10°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	4000K	15°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	4000K	30°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	Black	Black	4000K	45°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	White	Black	2700K	10°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	
DOT.R280	Recessed	20W	240V	(W) 45mm (H) 28mm 49mm x (L) 280mm	(W) 37mm (L) 275mm	White	Black	2700K	15°	Aluminium	IP23	<19	1350lm	>92+	≥2 SDCM	50,000 hours	5 years	Recessed Remote	



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	2700K	30°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	2700K	45°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	3000K	10°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	3000K	15°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	3000K	30°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	3000K	45°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	3500K	10°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	3500K	15°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	3500K	30°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	3500K	45°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	4000K	10°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	4000K	15°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	4000K	30°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote
	DOT.R280	Recessed	20W	240V	(W) 45mm (H) 8mm 49mm x (L) 280mm	(W) 37mm (L) 273mm	White	Black	4000K	45°	Aluminium	IP23	<19		1350lm	>92+	≤2 SDCM	50,000 hours	5 years	Recessed Remote