




Mounting	Surface
Wattage	10W
Voltage	240V
Dimensions	(W) 34.5mm x (H) 72mm x (L) 137mm
Finish	Black, White
Inner Trim Finish	Black, White
CCT	2700K, 3000K, 3500K, 4000K
Beam Angle	10°, 15°, 30°, 45°
Material	Aluminium
Driver	In-built
IP Rating	IP20
Luminous Flux	650lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Accessories	Clear Filter, Frosted Filter, Vertical Filter, Woven Filter
Control Gear	TRIAC
Warranty	5 years
Luminaires Type	Surface
Luminous Flux lm	501-1000lm

Control Gear

Accessories

Clear Filter, Frosted Filter, Vertical Filter, Woven Filter

DOT.S137							
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR	

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S137	Surface	10W	240V	(W) 34.5mm x (H) 72mm x (L) 137mm	Black	Black	2700K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 34.5mm x (H) 72mm x (L) 137mm	Black	Black	2700K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	2700K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	2700K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	3000K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	3000K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	3000K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	3000K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	3500K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	3500K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	3500K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	3500K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	4000K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	Black	4000K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	Black	4000K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	Black	4000K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	White	2700K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	White	2700K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	White	2700K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	White	2700K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	White	3000K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	White	3000K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	White	3000K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	White	3000K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	White	3500K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	Black	White	3500K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	White	3500K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	White	3500K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	White	4000K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	White	4000K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	White	4000K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	Black	White	4000K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	White	Black	2700K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	White	Black	2700K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	White	Black	2700K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	White	Black	2700K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	White	Black	3000K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm (L) 137mm	White	Black	3000K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	Black	3000K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	Black	3000K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	Black	3500K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	Black	3500K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	Black	3500K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	Black	3500K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	Black	4000K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	Black	4000K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	Black	4000K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	Black	4000K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	White	2700K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	W) 44.5mm x (H) 7.2mm x (L) 137mm	White	White	2700K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	2700K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	2700K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	3000K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	3000K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	3000K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	3000K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	3500K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	3500K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	3500K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	3500K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	4000K	10°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S137	Surface	10W	240V	(W) 54.5mm x (H) 7.2mm x (L) 137mm	White	White	4000K	15°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years



Image



SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
DOT.S137	Surface	10W	240V	(W) 44.5mm x (H) 72mm x (L) 137mm	White	White	4000K	30°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years
DOT.S137	Surface	10W	240V	(W) 44.5mm x (H) 72mm x (L) 137mm	White	White	4000K	45°	Aluminium	In-built	IP20	650lm	>92+	<2 SDCM	50,000 hours	5 years

