




Mounting	Surface
Wattage	4W
Voltage	240V
Dimensions	(W) 34.5mm x (H) 80mm x (L) 64.7mm
Finish	Black, White
Inner Trim Finish	Black, White
CCT	2700K, 3000K, 3500K, 4000K
Beam Angle	15°, 30°, 45°
Material	Aluminium
Driver	In-built
IP Rating	IP20
Luminous Flux	310lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Accessories	Clear Filter, Frosted Filter, Vertical Filter, Woven Filter
Control Gear	TRIAC
Warranty	5 years
Luminaires Type	Surface
Luminous Flux lm	1-500lm

Control Gear

Accessories
Clear Filter, Frosted Filter, Vertical Filter, Woven Filter

DOT.S65							
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR	

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S65	Surface	4W	240V	(W) 34.5mm x (H) 80mm x (L) 64.7mm	Black	Black	2700K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 34.5mm x (H) 80mm x (L) 64.7mm	Black	Black	2700K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	Black	2700K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	Black	3000K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	Black	3000K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	Black	3000K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	Black	3500K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	Black	3500K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	Black	3500K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	Black	4000K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	Black	4000K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	Black	4000K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	2700K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	2700K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	2700K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	3000K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	3000K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	3000K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	3500K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	3500K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	3500K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	4000K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	4000K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	Black	White	4000K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	2700K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	2700K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	2700K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	3000K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	3000K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	3000K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	3500K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	3500K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	3500K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	4000K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	4000K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	Black	4000K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	2700K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	2700K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	2700K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	3000K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	3000K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	3000K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	3500K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	3500K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	3500K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	4000K	15°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	4000K	30°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years
	DOT.S65	Surface	4W	240V	(W) 54.5mm x (H) 80mm x (L) 64.7mm	White	White	4000K	45°	Aluminium	In-built	IP20	310lm	>92+	<2 SDCM	50,000 hours	5 years