



<b>Mounting</b>	<u>Surface</u>
<b>Wattage</b>	<u>4W</u>
<b>Voltage</b>	<u>240V</u>
<b>Dimensions</b>	<u>(W) 34.5mm x (H) 80mm x (L) 64.7mm</u>
<b>Finish</b>	<u>Black, White</u>
<b>Inner Trim Finish</b>	<u>Black, White</u>
<b>CCT</b>	<u>2700K, 3000K, 3500K, 4000K</u>
<b>Beam Angle</b>	<u>15°, 30°, 45°</u>
<b>Material</b>	<u>Aluminium</u>
<b>Driver</b>	<u>In-built</u>
<b>IP Rating</b>	<u>IP20</u>
<b>Luminous Flux</b>	<u>310lm</u>
<b>CRI</b>	<u>&gt;92+</u>
<b>Colour Deviation</b>	<u>&lt;2 SDCM</u>
<b>Lifetime</b>	<u>50,000 hours</u>
<b>Accessories</b>	<u>Clear Filter, Frosted Filter, Vertical Filter, Woven Filter</u>
<b>Control Gear</b>	<u>Phase-Cut</u>
<b>Warranty</b>	<u>5 years</u>
<b>Luminaires Type</b>	<u>Surface</u>
<b>Luminous Flux lm</b>	<u>1-500lm</u>

Control Gear

Accessories

Clear Filter, Frosted Filter, Vertical Filter, Woven Filter

DOT.S65							
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR	

## VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S65	Surface	4W	240V	(W) 34.5mm x (H) 80mm x (L) 64.7mm	Black	Black	2700K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	(W) 34.5mm x (H) 80mm x (L) 64.7mm	Black	Black	2700K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	Black	2700K	45°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	Black	3000K	15°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	Black	3000K	30°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	Black	3000K	45°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	Black	3500K	15°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	Black	3500K	30°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	Black	3500K	45°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	Black	4000K	15°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	Black	4000K	30°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	Black	4000K	45°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	White	2700K	15°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	W) 44.5mm x H) 80mm x L) 64.7mm	Black	White	2700K	30°	Aluminium	IP20	310lm	>92+	≥2	SDCM	50,000 hours	5 years	In-built



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	Black	White	2700K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	Black	White	3000K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	Black	White	3000K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	Black	White	3000K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	Black	White	3500K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	Black	White	3500K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	Black	White	3500K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	Black	White	4000K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	Black	White	4000K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	Black	White	4000K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	2700K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	2700K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	2700K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	3000K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	3000K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	3000K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	3500K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	3500K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	3500K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	4000K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	4000K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	Black	4000K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	White	2700K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	DOT.S65	Surface	4W	240V	44.5mm x (H) 80mm x (L) 64.7mm	White	White	2700K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
DOT.S65	Surface	4W	240V	44.5mm x 80mm x 64.7mm	White	White	2700K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
DOT.S65	Surface	4W	240V	44.5mm x 80mm x 64.7mm	White	White	3000K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
DOT.S65	Surface	4W	240V	44.5mm x 80mm x 64.7mm	White	White	3000K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
DOT.S65	Surface	4W	240V	44.5mm x 80mm x 64.7mm	White	White	3000K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
DOT.S65	Surface	4W	240V	44.5mm x 80mm x 64.7mm	White	White	3500K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
DOT.S65	Surface	4W	240V	44.5mm x 80mm x 64.7mm	White	White	3500K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
DOT.S65	Surface	4W	240V	44.5mm x 80mm x 64.7mm	White	White	3500K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
DOT.S65	Surface	4W	240V	44.5mm x 80mm x 64.7mm	White	White	4000K	15°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
DOT.S65	Surface	4W	240V	44.5mm x 80mm x 64.7mm	White	White	4000K	30°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
DOT.S65	Surface	4W	240V	44.5mm x 80mm x 64.7mm	White	White	4000K	45°	Aluminium	IP20	310lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built

