



Mounting	<u>Recessed</u>
Wattage	<u>6W</u>
Voltage	<u>240V</u>
Dimensions	<u>(D) Ø38mm x (H) 83mm</u>
Cut Out Dimensions	<u>(D) Ø35mm</u>
Finish	<u>Black, White</u>
Inner Trim Finish	<u>Custom, Matte Black, Matte Silver, Matte White</u>
CCT	<u>2700K, 3000K, 3500K, 4000K</u>
Beam Angle	<u>15°, 24°, 36°</u>
Material	<u>Aluminium</u>
Driver	<u>Remote</u>
IP Rating	<u>IP20</u>
UGR	<u><19</u>
Luminous Flux	<u>375lm</u>
CRI	<u>>92+</u>
Colour Deviation	<u><2 SDCM</u>
Lifetime	<u>50,000 hours</u>
Accessories	<u>Honeycomb Lens, Soft Lens, Diffuser Lens</u>
Control Gear	<u>DALI, Phase-Cut</u>
Warranty	<u>5 years</u>
Luminaires Type	<u>Recessed</u>
Luminous Flux lm	<u>1-500lm</u>

Control Gear

Accessories

Honeycomb Lens, Soft Lens, Diffuser Lens

HIRO.AGTR38						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 83mm	(D) Ø35mm	Black	Custom	2700K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 83mm	(D) Ø35mm	Black	Custom	2700K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 83mm	(D) Ø35mm	Black	Custom	2700K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Custom	3000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Custom	3000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Custom	3000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Custom	3500K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Custom	3500K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Custom	3500K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Custom	4000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Custom	4000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Custom	4000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	2700K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	2700K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	2700K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	3000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	3000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	3000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	3500K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	3500K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	3500K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	4000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	4000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Black	4000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	2700K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	2700K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	2700K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	3000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	3000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	3000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	3500K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	3500K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	3500K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	4000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	4000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte Silver	4000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	2700K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	2700K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	2700K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	3000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	3000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	3000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	3500K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	3500K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	3500K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	4000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	4000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	Black	Matte White	4000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	2700K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	2700K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	2700K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	3000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	3000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	3000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	3500K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	3500K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	3500K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	4000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	4000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Custom	4000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	2700K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	2700K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	2700K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	3000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	3000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	3000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	3500K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	3500K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	3500K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	4000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	4000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Black	4000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	2700K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	2700K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	2700K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	3000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	3000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	3000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	3500K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	3500K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	3500K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	4000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	4000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte Silver	4000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	2700K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	2700K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	2700K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	3000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	3000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	3000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	3500K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	3500K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	3500K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	4000K	15°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	4000K	24°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years
	HIRO.AGTR38	Recessed	6W	240V	(D) Ø38mm (H) 85mm	(D) Ø35mm	White	Matte White	4000K	36°	Aluminium	Remote	IP20	<19	375lm	>92+	<2 SDCM	50,000 hours	5 years