



Mounting	<u>Surface</u>
Wattage	<u>30W</u>
Voltage	<u>240V</u>
Dimensions	<u>(W) Ø104mm x (H) 142mm</u>
Finish	<u>Black, White</u>
Inner Trim Finish	<u>Anthracite</u>
CCT	<u>2700K, 3000K, 3500K, 4000K</u>
Beam Angle	<u>15°, 24°, 36°</u>
Material	<u>Aluminium</u>
Driver	<u>In-built</u>
IP Rating	<u>IP20</u>
UGR	<u><19</u>
Luminous Flux	<u>2550lm</u>
CRI	<u>>92+</u>
Colour Deviation	<u><2 SDCM</u>
Lifetime	<u>35,000 hours</u>
Control Gear	<u>TRIAC</u>
Warranty	<u>5 years</u>
Luminaires Type	<u>Surface</u>
Luminous Flux lm	<u>2501-3000lm</u>

Control Gear

Accessories

PRODUCT NAME WATTAGE FINISH INNER TRIM FINISH CCT BEAM ANGLE CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	KAN.C104	Surface	30W	240V	Ø1104mm x (H) 142mm	Black	Anthracite	2700K	15°	Aluminium	In-built	IP20	<19	2550lm	>92+	<2 SDCM	Any Lifetime	5 years
	KAN.C104	Surface	30W	240V	Ø1104mm x (H) 142mm	Black	Anthracite	2700K	24°	Aluminium	In-built	IP20	<19	2550lm	>92+	<2 SDCM	Any Lifetime	5 years
	KAN.C104	Surface	30W	240V	Ø1104mm x (H) 142mm	Black	Anthracite	2700K	36°	Aluminium	In-built	IP20	<19	2550lm	>92+	<2 SDCM	Any Lifetime	5 years



Image

SKU Mounting Wattage Voltage Dimensions Finish Inner Trim Finish CCT Beam Angle Material Driver IP Rating UGR Luminous Flux CRI Colour Deviation Lifetime Warranty



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm Black Anthracite 3000K 15° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm Black Anthracite 3000K 24° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm Black Anthracite 3000K 36° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm Black Anthracite 3500K 15° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm Black Anthracite 3500K 24° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm Black Anthracite 3500K 36° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm Black Anthracite 4000K 15° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm Black Anthracite 4000K 24° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm Black Anthracite 4000K 36° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm White Anthracite 2700K 15° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm White Anthracite 2700K 24° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm White Anthracite 2700K 36° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



KAN.C104 Surface 30W 240V Ø104mm x (H) 142mm White Anthracite 3000K 15° Aluminium In-built IP20 <19 2550lm >92+ <2 SDCM Any Lifetime 5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	KAN.C104	Surface	30W	240V	Ø104mm x (H) 142mm	White Anthracite	Anthracite	3000K	24°	Aluminium	In-built	IP20	<19	2550lm	>92+	<2 SDCM	Any Lifetime	5 years
	KAN.C104	Surface	30W	240V	Ø104mm x (H) 142mm	White Anthracite	Anthracite	3000K	36°	Aluminium	In-built	IP20	<19	2550lm	>92+	<2 SDCM	Any Lifetime	5 years
	KAN.C104	Surface	30W	240V	Ø104mm x (H) 142mm	White Anthracite	Anthracite	3500K	15°	Aluminium	In-built	IP20	<19	2550lm	>92+	<2 SDCM	Any Lifetime	5 years
	KAN.C104	Surface	30W	240V	Ø104mm x (H) 142mm	White Anthracite	Anthracite	3500K	24°	Aluminium	In-built	IP20	<19	2550lm	>92+	<2 SDCM	Any Lifetime	5 years
	KAN.C104	Surface	30W	240V	Ø104mm x (H) 142mm	White Anthracite	Anthracite	3500K	36°	Aluminium	In-built	IP20	<19	2550lm	>92+	<2 SDCM	Any Lifetime	5 years
	KAN.C104	Surface	30W	240V	Ø104mm x (H) 142mm	White Anthracite	Anthracite	4000K	15°	Aluminium	In-built	IP20	<19	2550lm	>92+	<2 SDCM	Any Lifetime	5 years
	KAN.C104	Surface	30W	240V	Ø104mm x (H) 142mm	White Anthracite	Anthracite	4000K	24°	Aluminium	In-built	IP20	<19	2550lm	>92+	<2 SDCM	Any Lifetime	5 years
	KAN.C104	Surface	30W	240V	Ø104mm x (H) 142mm	White Anthracite	Anthracite	4000K	36°	Aluminium	In-built	IP20	<19	2550lm	>92+	<2 SDCM	Any Lifetime	5 years