



Mounting	Surface
Wattage	15W
Voltage	240V
Dimensions	(W) Ø92mm x (H) 125mm
Finish	Black, White
Inner Trim Finish	Anthracite
CCT	2700K, 3000K, 3500K, 4000K
Beam Angle	15°, 24°, 36°
Material	Aluminium
Driver	In-built
IP Rating	IP20
UGR	<19
Luminous Flux	1275lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Control Gear	TRIAC
Warranty	5 years
Luminaires Type	Surface
Luminous Flux lm	1001-1500lm

Control Gear

Accessories

```
graph LR; A[KAN,C92] --- B[ ]; B --- C[ ]; C --- D[ ]; D --- E[ ]; E --- F[ ]; F --- G[ ];
```

PRODUCT NAME WATTAGE FINISH INNER TRIM FINISH CCT BEAM ANGLE CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	KAN.C92	Surface	15W	240V	(W) 292mm x (H) 125mm	Black	Anthracite	2700K	15°	Aluminium	In-built	IP20	<19	1275lm	>92+	<2 SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	(W) 292mm x (H) 125mm	Black	Anthracite	2700K	24°	Aluminium	In-built	IP20	<19	1275lm	>92+	<2 SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	(W) 292mm x (H) 125mm	Black	Anthracite	2700K	36°	Aluminium	In-built	IP20	<19	1275lm	>92+	<2 SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	Black	Anthracite	3000K	15°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	Black	Anthracite	3000K	24°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	Black	Anthracite	3000K	36°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	Black	Anthracite	3500K	15°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	Black	Anthracite	3500K	24°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	Black	Anthracite	3500K	36°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	Black	Anthracite	4000K	15°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	Black	Anthracite	4000K	24°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	Black	Anthracite	4000K	36°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White	Anthracite	2700K	15°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White	Anthracite	2700K	24°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White	Anthracite	2700K	36°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White	Anthracite	3000K	15°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White Anthracite		3000K	24°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White Anthracite		3000K	36°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White Anthracite		3500K	15°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White Anthracite		3500K	24°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White Anthracite		3500K	36°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White Anthracite		4000K	15°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White Anthracite		4000K	24°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years
	KAN.C92	Surface	15W	240V	Ø92mm x (H) 125mm	White Anthracite		4000K	36°	Aluminium	In-built	IP20	<19	1275lm	>92+ <2	SDCM	50,000 hours	5 years