



Mounting	48V Magnetic Track
Wattage	6W
Voltage	DC48V
Dimensions	(H) 98mm x (L) 111.5mm
Finish	Black
CCT	2700K, 3000K, 3500K, 4000K
Beam Angle	24°, 38°
Material	Aluminium
Driver	Remote
IP Rating	IP20
Luminous Flux	402lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Control Gear	1-10V, DALI
Warranty	5 years
Luminaires Type	Track Mounted – Track Luminaires
Luminous Flux lm	1-500lm

Control Gear

Accessories

LOOR.LAS113						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS








Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm x (L) 111.5mm	Black	2700K	24°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm x (L) 111.5mm	Black	2700K	24°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	2700K	38°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	2700K	38°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	3000K	24°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	3000K	24°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	3000K	38°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	3000K	38°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	3500K	24°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	3500K	24°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	3500K	38°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	3500K	38°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	4000K	24°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
	LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	4000K	24°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years



Image



SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	4000K	38°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years



LOOR.LAS113	Any Mounting	6W	DC48V	(H) 98mm (L) 111.5mm	Black	4000K	38°	Any Material	Remote	IP20	402lm	>92+	<2 SDCM	Any Lifetime	5 years
-------------	--------------	----	-------	-------------------------	-------	-------	-----	--------------	--------	------	-------	------	---------	--------------	---------