



LOOR LINEAR DIFFUSED 300

LOOR.LSD300.....

Collections, Loor, Luminaires Type, Track Mounted



Mounting	48V Magnetic Track
Wattage	7W
Voltage	DC48V
Dimensions	(H) 25mm x (L) 300mm
Finish	Black
CCT	2700K, 3000K, 3500K, 4000K
Beam Angle	110°
Material	Aluminium
Driver	Remote
IP Rating	IP20
Luminous Flux	350lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Control Gear	1-10V, DALI
Warranty	5 years
Luminaires Type	Track Mounted – Track Luminaires
Luminous Flux lm	1-500lm

Control Gear

Accessories

LOOR.LSD300						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty
	LOOR.LSD300	48V Magnetic Track	7W	DC48V	(H) 25mm x (L) 300mm	Black	2700K	110°	Aluminium	Remote	IP20	350lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years
	LOOR.LSD300	48V Magnetic Track	7W	DC48V	(H) 25mm x (L) 300mm	Black	2700K	110°	Aluminium	Remote	IP20	350lm	>92+	<2 SDCM	50,000 hours	DALI	5 years



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty
LOOR.LSD300	48V Magnetic Track	7W	DC48V	(H) 25mm (L) 300mm	Black	3000K	110°	Aluminium	Remote	IP20	350lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years
LOOR.LSD300	48V Magnetic Track	7W	DC48V	(H) 25mm (L) 300mm	Black	3000K	110°	Aluminium	Remote	IP20	350lm	>92+	<2 SDCM	50,000 hours	DALI	5 years
LOOR.LSD300	48V Magnetic Track	7W	DC48V	(H) 25mm (L) 300mm	Black	3500K	110°	Aluminium	Remote	IP20	350lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years
LOOR.LSD300	48V Magnetic Track	7W	DC48V	(H) 25mm (L) 300mm	Black	3500K	110°	Aluminium	Remote	IP20	350lm	>92+	<2 SDCM	50,000 hours	DALI	5 years
LOOR.LSD300	48V Magnetic Track	7W	DC48V	(H) 25mm (L) 300mm	Black	4000K	110°	Aluminium	Remote	IP20	350lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years
LOOR.LSD300	48V Magnetic Track	7W	DC48V	(H) 25mm (L) 300mm	Black	4000K	110°	Aluminium	Remote	IP20	350lm	>92+	<2 SDCM	50,000 hours	DALI	5 years