



Mounting	48V Magnetic Track
Voltage	DC48V
Wattage	15W
Dimensions	(D) Ø38mm x (L) 300mm
Overall Length	211mm
Finish	Black, Brass, White
Inner Trim Finish	Brass
CCT	2700K, 3000K, 4000K
Beam Angle	38°
Material	Aluminium
Driver	Remote
IP Rating	IP20
Luminous Flux	1005lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Control Gear	1-10V, DALI
Warranty	5 years
Luminaires Type	Track Mounted – Track Luminaires
Luminous Flux lm	1001-1500lm

Control Gear

Accessories

LOOR.LP55						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Voltage	Wattage	Dimensions	Overall Length	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm x (L) 300mm	211mm	Black	Brass	2700K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm x (L) 300mm	211mm	Black	Brass	2700K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	DALI	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm x (L) 300mm	211mm	Black	Brass	3000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years



Image	SKU	Mounting	Voltage	Wattage	Dimensions	Overall Length	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	Black	Brass	3000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	DALI	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	Black	Brass	4000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	Black	Brass	4000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	DALI	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	Brass	Brass	2700K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	Brass	Brass	2700K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	DALI	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	Brass	Brass	3000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	Brass	Brass	3000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	DALI	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	Brass	Brass	4000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	Brass	Brass	4000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	DALI	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	White	Brass	2700K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	White	Brass	2700K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	DALI	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	White	Brass	3000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	White	Brass	3000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	DALI	5 years
	LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	White	Brass	4000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	1-10V	5 years



Image



SKU	Mounting	Voltage	Wattage	Dimensions	Overall Length	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty
LOOR.LP55	48V Magnetic Track	DC48V	15W	(D) Ø38mm (L) 300mm	211mm	White	Brass	4000K	38°	Aluminium	Remote	IP20	1005lm	>92+	<2 SDCM	50,000 hours	DALI	5 years