



Mounting	48V Magnetic Track
Wattage	2x10W
Voltage	DC48V
Dimensions	(D) Ø38.5mm x (L) 105mm
Overall Length	129mm
Finish	Black, White
Inner Trim Finish	Black, White
CCT	2700K, 3000K, 3500K, 4000K
Beam Angle	15°, 24°, 38°
Material	Aluminium
Driver	Remote
IP Rating	IP20
Luminous Flux	1504lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Control Gear	Non-dimmable
Warranty	5 years
Luminaires Type	Track Mounted – Track Luminaires
Luminous Flux lm	1501-2000lm

Control Gear

Accessories

LOOR.ST38						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Overall Length	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) Ø38.5mm x (L) 105mm	129mm	Black	Black	2700K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) Ø38.5mm x (L) 105mm	129mm	Black	Black	2700K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Overall Length	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	Black	2700K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	Black	3000K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	Black	3000K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	Black	3000K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	Black	3500K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	Black	3500K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	Black	3500K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	Black	4000K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	Black	4000K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	Black	4000K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	2700K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	2700K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Overall Length	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	2700K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	3000K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	3000K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	3000K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	3500K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	3500K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	3500K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	4000K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	4000K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	Black	White	4000K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	2700K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	2700K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Overall Length	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	2700K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	3000K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	3000K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	3000K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	3500K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	3500K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	3500K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	4000K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	4000K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	Black	4000K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	White	2700K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x (L) 105mm	129mm	White	White	2700K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Overall Length	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x 129mm (L) 105mm	White	White	White	2700K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x 129mm (L) 105mm	White	White	White	3000K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x 129mm (L) 105mm	White	White	White	3000K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x 129mm (L) 105mm	White	White	White	3000K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x 129mm (L) 105mm	White	White	White	3500K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x 129mm (L) 105mm	White	White	White	3500K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x 129mm (L) 105mm	White	White	White	3500K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x 129mm (L) 105mm	White	White	White	4000K	15°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x 129mm (L) 105mm	White	White	White	4000K	24°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours
	LOOR.ST38	48V Magnetic Track	2x10W	DC48V	(D) 38.5mm x 129mm (L) 105mm	White	White	White	4000K	38°	Aluminium	Remote	IP20	1504lm	>92+	<2 SDCM	50,000 hours