



Wattage	9.6W/m
Voltage	DC24V
Dimensions	(W) 3.5mm
Cut Length	37.5mm
CCT	2700K, 3000K, 3500K, 4000K, 5000K
Beam Angle	120°
Driver	Remote
IP Rating	IP20
Luminous Flux	1000lm/m
CRI	>92+, >98
Colour Deviation	<3 SDCM
Control Gear	1-10V, DALI, Non-dimmable, TRIAC
Warranty	5 years
Luminaires Type	Linear Systems – Linear Light Source

Control Gear

Accessories

LYNE.MC96						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	2700K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	2700K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	2700K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	2700K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	2700K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	2700K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	2700K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	2700K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3500K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3500K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3500K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3500K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3500K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3500K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3500K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	3500K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	4000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	4000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	4000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	4000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	4000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	4000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	4000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	4000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	5000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	5000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	5000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	5000K	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	5000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	5000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	5000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.MC96	9.6W/m	DC24V	(W) 3.5mm	37.5mm	5000K	120°	Remote	IP20	1000lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source