



Wattage	20W/m
Voltage	DC24V
Dimensions	(W) 12mm
Cut Length	50mm
CCT	RGB
Beam Angle	120°
Driver	Remote
IP Rating	IP20, IP67
Luminous Flux	1000lm/m
CRI	>92+, >98
Colour Deviation	<3 SDCM
Control Gear	1-10V, DALI, Non-dimmable, TRIAC
Warranty	5 years
Luminaires Type	Linear Systems – Linear Light Source

Control Gear

Accessories

LYNE.RGB						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.RGB	20W/m	DC24V	(W) 12mm	50mm	RGB	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.RGB	20W/m	DC24V	(W) 12mm	50mm	RGB	120°	Remote	IP20	1000lm/m	>92+	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP20	1000lm/m	>92+ <3 SDCM	Non-dimmable	5 years				Linear Systems - Linear Light Source
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP20	1000lm/m	>92+ <3 SDCM	TRIAC			5 years		Linear Systems - Linear Light Source
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP20	1000lm/m	>98 <3 SDCM	1-10V			5 years		Linear Systems - Linear Light Source
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP20	1000lm/m	>98 <3 SDCM	DALI			5 years		Linear Systems - Linear Light Source
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP20	1000lm/m	>98 <3 SDCM	Non-dimmable	5 years				Linear Systems - Linear Light Source
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP20	1000lm/m	>98 <3 SDCM	TRIAC			5 years		Linear Systems - Linear Light Source
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP67	1000lm/m	>92+ <3 SDCM	1-10V			5 years		Linear Systems - Linear Light Source
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP67	1000lm/m	>92+ <3 SDCM	DALI			5 years		Linear Systems - Linear Light Source
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP67	1000lm/m	>92+ <3 SDCM	Non-dimmable	5 years				Linear Systems - Linear Light Source
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP67	1000lm/m	>92+ <3 SDCM	TRIAC			5 years		Linear Systems - Linear Light Source
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP67	1000lm/m	>98 <3 SDCM	1-10V			5 years		Linear Systems - Linear Light Source
	LYNE.RGB 20W/m	DC24V	(W) 12mm	50mm	RGB 120°	Remote	IP67	1000lm/m	>98 <3 SDCM	DALI			5 years		Linear Systems - Linear Light Source



Image

SKU Wattage Voltage Dimensions Cut Length CCT Beam Angle Driver IP Rating Luminous Flux CRI Colour Deviation Control Gear Warranty Luminaires Type



LYNE.RGB 20W/m DC24V (W) 12mm 50mm RGB 120° Remote IP67 1000lm/m >98 <3 SDCM Non-dimmable 5 years Linear Systems - Linear Light Source



LYNE.RGB 20W/m DC24V (W) 12mm 50mm RGB 120° Remote IP67 1000lm/m >98 <3 SDCM TRIAC 5 years Linear Systems - Linear Light Source