



Wattage	<u>20W/m</u>
Voltage	<u>DC24V</u>
Dimensions	<u>(W) 12mm</u>
Cut Length	<u>71.4mm</u>
CCT	<u>RGBW</u>
Beam Angle	<u>120°</u>
Driver	<u>Remote</u>
IP Rating	<u>IP20, IP67</u>
Luminous Flux	<u>630lm/W</u>
CRI	<u>>92+, >98</u>
Colour Deviation	<u><3 SDCM</u>
Control Gear	<u>DMX, RGBW Controller</u>
Warranty	<u>5 years</u>
Luminaires Type	<u>Linear Systems – Linear Light Source</u>
Luminous Flux lm	501-1000lm

Control Gear

Accessories

LYNE.RGBW						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Control Gear	Warranty	Luminaires Type
	LYNE.RGBW	20W/m	DC24V	(W) 12mm	71.4mm	RGBW	120°	Remote	IP20	630lm/W	>92+	DMX	5 years	Linear Systems - Linear Light Source
	LYNE.RGBW	20W/m	DC24V	(W) 12mm	71.4mm	RGBW	120°	Remote	IP20	630lm/W	>92+	RGBW Controller	5 years	Linear Systems - Linear Light Source



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Control Gear	Warranty	Luminaires Type
	LYNE.RGBW 20W/m	DC24V	(W) 12mm	71.4mm RGBW	120°	Remote	IP20	630lm/W	>98	DMX	5 years	Linear Systems - Linear Light Source		
	LYNE.RGBW 20W/m	DC24V	(W) 12mm	71.4mm RGBW	120°	Remote	IP20	630lm/W	>98	RGBW Controller	5 years	Linear Systems - Linear Light Source		
	LYNE.RGBW 20W/m	DC24V	(W) 12mm	71.4mm RGBW	120°	Remote	IP67	630lm/W	>92+	DMX	5 years	Linear Systems - Linear Light Source		
	LYNE.RGBW 20W/m	DC24V	(W) 12mm	71.4mm RGBW	120°	Remote	IP67	630lm/W	>92+	RGBW Controller	5 years	Linear Systems - Linear Light Source		
	LYNE.RGBW 20W/m	DC24V	(W) 12mm	71.4mm RGBW	120°	Remote	IP67	630lm/W	>98	DMX	5 years	Linear Systems - Linear Light Source		
	LYNE.RGBW 20W/m	DC24V	(W) 12mm	71.4mm RGBW	120°	Remote	IP67	630lm/W	>98	RGBW Controller	5 years	Linear Systems - Linear Light Source		