



Wattage	14.4W/m
Voltage	DC24V
Dimensions	(W) 10mm
Cut Length	50mm
CCT	2700K, 3000K, 3500K, 4000K, 5000K
Beam Angle	120°
Driver	Remote
IP Rating	IP20, IP67, IP68
Luminous Flux	1512lm/m
CRI	>98
Colour Deviation	<3 SDCM
Control Gear	1-10V, DALI, Non-dimmable, TRIAC
Warranty	5 years
Luminaires Type	Linear Systems – Linear Light Source
Luminous Flux lm	1501-2000lm

Control Gear

Accessories

LYNE.ST144						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	2700K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	3500K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	4000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Control Gear	Warranty	Luminaires Type
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP20	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP67	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	1-10V	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	DALI	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	Non-dimmable	5 years	Linear Systems - Linear Light Source
	LYNE.ST144	14.4W/m	DC24V	(W) 10mm	50mm	5000K	120°	Remote	IP68	1512lm/m	>98	<3 SDCM	TRIAC	5 years	Linear Systems - Linear Light Source