



Mounting	<u>Suspended</u>
Wattage	<u>15W</u>
Voltage	<u>240V</u>
Dimensions	<u>(D) Ø85mm x (H) 200mm</u>
Finish	<u>Black, White</u>
Inner Trim Finish	<u>Anthracite, Black, White</u>
CCT	<u>2700K, 3000K, 4000K, 5000K</u>
Beam Angle	<u>15°, 24°, 36°, 60°</u>
Material	<u>Aluminium</u>
Driver	<u>In-built</u>
IP Rating	<u>IP23</u>
Luminous Flux	<u>1330lm</u>
CRI	<u>>92+</u>
Colour Deviation	<u><2 SDCM</u>
Lifetime	<u>50,000 hours</u>
Accessories	<u>Honeycomb Lens, Soft Lens, Diffuser Lens, Tube</u>
Control Gear	<u>DALI, Phase-Cut</u>
Warranty	<u>5 years</u>
Luminaires Type	<u>Surface</u>
Luminous Flux lm	<u>1001-1500lm</u>

Control Gear

Accessories

Honeycomb Lens, Soft Lens, Diffuser Lens, Tube

MINO.SPR85							
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR	

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm x (H) 200mm	Black	Anthracite	2700K	15°	Aluminium	IP23	IP23	1330lm	>92+	<2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm x (H) 200mm	Black	Anthracite	2700K	24°	Aluminium	IP23	IP23	1330lm	>92+	<2 SDCM	50,000 hours	5 years	In-built



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	2700K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	2700K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	3000K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	3000K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	3000K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	3000K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	4000K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	4000K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	4000K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	4000K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	5000K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	5000K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	5000K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Anthracite	5000K	60°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	2700K	15°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	2700K	24°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	2700K	36°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	2700K	60°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	3000K	15°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	3000K	24°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	3000K	36°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	3000K	60°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	4000K	15°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	4000K	24°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	4000K	36°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	4000K	60°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	5000K	15°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	5000K	24°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	5000K	36°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	Black	5000K	60°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	2700K	15°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	2700K	24°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	2700K	36°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	2700K	60°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	3000K	15°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	3000K	24°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	3000K	36°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	3000K	60°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	4000K	15°	Aluminium	IP23	1330lm	>92+	≥2	SDCM	50,000 hours	5 years In-built



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	4000K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	4000K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	4000K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	5000K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	5000K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	5000K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	Black	White	5000K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Anthracite	2700K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Anthracite	2700K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Anthracite	2700K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Anthracite	2700K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Anthracite	3000K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Anthracite	3000K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Anthracite		3000K	36°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Anthracite		3000K	60°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Anthracite		4000K	15°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Anthracite		4000K	24°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Anthracite		4000K	36°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Anthracite		4000K	60°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Anthracite		5000K	15°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Anthracite		5000K	24°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Anthracite		5000K	36°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Anthracite		5000K	60°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Black		2700K	15°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Black		2700K	24°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White Black		2700K	36°	Aluminium	IP23		1330lm >92+	≤2 SDCM	50,000 hours	5 years	In-built



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	2700K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	3000K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	3000K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	3000K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	3000K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	4000K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	4000K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	4000K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	4000K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	5000K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	5000K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	5000K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	Black	5000K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	2700K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	2700K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	2700K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	2700K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	3000K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	3000K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	3000K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	3000K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	4000K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	4000K	24°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	4000K	36°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	4000K	60°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built
	MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	5000K	15°	Aluminium	IP23	1330lm	>92+	≤2 SDCM	50,000 hours	5 years	In-built



Image



SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	5000K	24°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	5000K	36°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built
MINO.SPR85	Suspended	15W	240V	(D) Ø85mm (H) 200mm	White	White	5000K	60°	Aluminium	IP23	1330lm	>92+	≥2 SDCM	50,000 hours	5 years	In-built

