

LS

MINO.SPR65.....

MINO.SUSPENDED R65

Luminaires Type, Suspended



Mounting	Suspended
Wattage	12W
Voltage	240V
Dimensions	(D) Ø65mm x (H) 250mm
Finish	Black, White
Inner Trim Finish	Anthracite, Black, White
CCT	2700K, 3000K, 4000K, 5000K
Beam Angle	15°, 24°, 36°, 60°
Material	Aluminium
Driver	In-built
IP Rating	IP23
Luminous Flux	1080lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Accessories	Honeycomb Lense, Soft Lense, Diffuser Lense, Tube
Control Gear	DALI, TRIAC
Warranty	5 years
Luminaires Type	Surface
Luminous Flux lm	1001-1500lm

Control Gear

Accessories
Honeycomb Lense, Soft Lense, Diffuser Lense, Tube

MINO.SPR65						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR65	Suspended	12W	240V	(D) Ø65mm x (H) 250mm	Black	Anthracite	2700K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
	MINO.SPR65	Suspended	12W	240V	(D) Ø65mm x (H) 250mm	Black	Anthracite	2700K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	2700K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	2700K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	3000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	3000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	3000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	3000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	4000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	4000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	4000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	4000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	5000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	5000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	5000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years



Image



SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Anthracite	5000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	2700K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	2700K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	2700K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	2700K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	3000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	3000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	3000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	3000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	4000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	4000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	4000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	4000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years



Image



SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	5000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	5000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	5000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	Black	5000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	2700K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	2700K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	2700K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	2700K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	3000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	3000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	3000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	3000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	4000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years



Image



SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	4000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	4000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	4000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	5000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	5000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	5000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	Black	White	5000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Anthracite	2700K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Anthracite	2700K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Anthracite	2700K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Anthracite	2700K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Anthracite	3000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Anthracite	3000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years



Image



SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Anthracite		3000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Anthracite		3000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Anthracite		4000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Anthracite		4000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Anthracite		4000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Anthracite		4000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Anthracite		5000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Anthracite		5000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Anthracite		5000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Anthracite		5000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Black		2700K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Black		2700K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White Black		2700K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years



Image



SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	2700K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	3000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	3000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	3000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	3000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	4000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	4000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	4000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	4000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	5000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	5000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	5000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	Black	5000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years



Image



SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Upper Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	2700K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	2700K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	2700K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	2700K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	3000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	3000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	3000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	3000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	4000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	4000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	4000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	4000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	5000K	15°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years



SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Fin	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	5000K	24°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	5000K	36°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years
MINO.SPR65	Suspended	12W	240V	(D) Ø65mm (H) 250mm	White	White	5000K	60°	Aluminium	In-built	IP23	1080lm	>92+	<2 SDCM	50,000 hours	5 years