



Mounting	<u>Suspended</u>
Wattage	<u>20W</u>
Voltage	<u>240V</u>
Dimensions	<u>(D) Ø96mm x (H) 200mm</u>
Finish	<u>Black, White</u>
Inner Trim Finish	<u>Black, White</u>
CCT	<u>2700K, 3000K, 4000K, 5000K</u>
Beam Angle	<u>15°, 24°, 60°</u>
Material	<u>Aluminium, Brass, Copper</u>
IP Rating	<u>IP20</u>
Luminous Flux	<u>1841lm</u>
CRI	<u>>83+</u>
Colour Deviation	<u><3 SDCM</u>
Lifetime	<u>45,000 hours</u>
Accessories	<u>Honeycomb Lens, Soft Lens, Diffuser Lens, Tube</u>
Control Gear	<u>DALI, Phase-Cut</u>
Warranty	<u>5 years</u>
Luminaires Type	<u>Suspended</u>
Luminous Flux lm	<u>1501-2000lm</u>

Control Gear

Accessories

Honeycomb Lens, Soft Lens, Diffuser Lens, Tube

MINO.SPR96						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	2700K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	2700K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	2700K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	2700K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	2700K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	2700K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	2700K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	2700K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	2700K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	3000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	3000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	3000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	3000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	3000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years





Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	3000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	3000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	3000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	3000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	4000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	4000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	4000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	4000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	4000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	4000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	4000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	4000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	4000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	5000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	5000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	5000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	5000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	5000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	5000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	5000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	5000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	Black	5000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	2700K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	2700K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years





Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	2700K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	2700K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	2700K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	2700K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	2700K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	2700K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	2700K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	3000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	3000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	3000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	3000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	3000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years





Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	3000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	3000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	3000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	3000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	4000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	4000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	4000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	4000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	4000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	4000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	4000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	4000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	4000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	5000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	5000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	5000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	5000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	5000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	5000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	5000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	5000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	Black	White	5000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	2700K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	2700K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years





Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	2700K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	2700K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	2700K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	2700K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	2700K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	2700K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	2700K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	3000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	3000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	3000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	3000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	3000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years





Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	3000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	3000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	3000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	3000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	4000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	4000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	4000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	4000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	4000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	4000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	4000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	4000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	4000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	5000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	5000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	5000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	5000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	5000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	5000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	5000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	5000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	Black	5000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	2700K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	2700K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years





Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	2700K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	2700K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	2700K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	2700K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	2700K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	2700K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	2700K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	3000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	3000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	3000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	3000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	3000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years





Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	3000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	3000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	3000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	3000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	4000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	4000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	4000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	4000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	4000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	4000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	4000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	4000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years





Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	4000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	5000K	15°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	5000K	15°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	5000K	15°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	5000K	24°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	5000K	24°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	5000K	24°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	5000K	60°	Aluminium	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	5000K	60°	Brass	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years
	MINO.SPR96	Suspended	20W	240V	(D) Ø96mm (H) 200mm	White	White	5000K	60°	Copper	IP20	1841lm	>83+	<3 SDCM	45,000 hours	5 years