



<b>Mounting</b>	<u>Recessed</u>
<b>Wattage</b>	<u>1W</u>
<b>Voltage</b>	<u>DC48V</u>
<b>Dimensions</b>	<u>(D) Ø21mm x (H) 56mm</u>
<b>Cut Out Dimensions</b>	<u>(D) Ø18mm</u>
<b>Finish</b>	<u>Black, White</u>
<b>CCT</b>	<u>2700K, 3000K, 3500K, 4000K</u>
<b>Beam Angle</b>	<u>15°, 24°</u>
<b>Material</b>	<u>Aluminium</u>
<b>Driver</b>	<u>Remote</u>
<b>IP Rating</b>	<u>IP20</u>
<b>UGR</b>	<u>&lt;19</u>
<b>Luminous Flux</b>	<u>42lm</u>
<b>CRI</b>	<u>&gt;92+</u>
<b>Colour Deviation</b>	<u>&lt;2 SDCM</u>
<b>Lifetime</b>	<u>50,000 hours</u>
<b>Control Gear</b>	<u>1-10V, DALI, Non-dimmable</u>
<b>Warranty</b>	<u>5 years</u>
<b>Luminaires Type</b>	<u>Recessed</u>
<b>Luminous Flux lm</b>	<u>1-500lm</u>

Control Gear

Accessories

MIRO.DM21						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

## VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	MIRO.DM21 Recessed 1W			DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	Black	2700K	15°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21 Recessed 1W			DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	Black	2700K	24°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21 Recessed 1W			DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	Black	3000K	15°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	Black	3000K	24°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	Black	3500K	15°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	Black	3500K	24°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	Black	4000K	15°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	Black	4000K	24°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	White	2700K	15°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	White	2700K	24°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	White	3000K	15°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	White	3000K	24°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	White	3500K	15°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	White	3500K	24°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	White	4000K	15°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MIRO.DM21	Recessed	1W	DC48V	(D) Ø21mm (H) 56mm	(D) Ø18mm	White	4000K	24°	Aluminium	Remote	IP20	<19	42lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed