

LS MODO ANTI-GLARE TRIMLESS FIXED R165

Collections, Luminaires Type, Modo, Recessed



Mounting	<u>Plaster Recessed</u>
Wattage	<u>42W</u>
Voltage	<u>240V</u>
Dimensions	<u>(D) Ø147mm x (H) 184mm</u>
Cut Out Dimensions	<u>(D) Ø148mm</u>
Finish	<u>Black, White</u>
Inner Trim Finish	<u>Anthracite, Chrome, Custom, Matte Black, Matte Silver, Matte White</u>
CCT	<u>2700K, 3000K, 3500K, 4000K</u>
Beam Angle	<u>15°, 24°, 38°, 50°</u>
Material	<u>Aluminium</u>
Driver	<u>Remote</u>
IP Rating	<u>IP20</u>
UGR	<u><19</u>
Luminous Flux	<u>3570lm</u>
CRI	<u>>92+</u>
Colour Deviation	<u><2 SDCM</u>
Lifetime	<u>50,000 hours</u>
Accessories	<u>Honeycomb Lens, Soft Lens</u>
Control Gear	<u>DALI, Phase-Cut</u>
Warranty	<u>5 years</u>
Luminaires Type	<u>Recessed</u>
Luminous Flux lm	<u>3001+lm</u>

Control Gear

Accessories

Honeycomb Lens, Soft Lens

MODO.AGTR165						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTR165	<u>Plaster Recessed</u>	42W	240V	<u>(D) Ø147mm x (H) 184mm</u>	<u>(D) Ø148mm</u>	Black	Anthracite	2700K	15°	Aluminium	IP20	<19	3570lm	>92+	<u>≤2 SDCM</u>	<u>50,000 hours</u>	5 years	Remote
	MODO.AGTR165	<u>Plaster Recessed</u>	42W	240V	<u>(D) Ø147mm x (H) 184mm</u>	<u>(D) Ø148mm</u>	Black	Anthracite	2700K	24°	Aluminium	IP20	<19	3570lm	>92+	<u>≤2 SDCM</u>	<u>50,000 hours</u>	5 years	Remote
	MODO.AGTR165	<u>Plaster Recessed</u>	42W	240V	<u>(D) Ø147mm x (H) 184mm</u>	<u>(D) Ø148mm</u>	Black	Anthracite	2700K	38°	Aluminium	IP20	<19	3570lm	>92+	<u>≤2 SDCM</u>	<u>50,000 hours</u>	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		2700K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		3000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		3000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		3000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		3000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		3500K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		3500K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		3500K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		4000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		4000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		4000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Anthracite		4000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		2700K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		2700K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		2700K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		2700K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		3000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		3000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		3000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		3000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		3500K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		3500K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		3500K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		4000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		4000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		4000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Chrome		4000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black Custom		2700K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	2700K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	2700K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	2700K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	3000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	3000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	3000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	3000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	3500K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	3500K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	3500K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	4000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	4000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	4000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Custom	4000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	2700K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	2700K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	2700K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	2700K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	3000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	3000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	3000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	3000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	3500K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	3500K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	3500K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	4000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	4000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	4000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Black	4000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	2700K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	2700K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	2700K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	2700K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	3000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	3000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	3000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	3000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	3500K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	3500K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	3500K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	4000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	4000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	4000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte Silver	4000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	2700K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	2700K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	2700K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	2700K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	3000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	3000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	3000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	3000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	3500K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	3500K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	3500K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	4000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	4000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	4000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	Black	Matte White	4000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	2700K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	2700K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	2700K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	2700K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	3000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	3000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	3000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	3000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	3500K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	3500K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Anthracite	3500K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Anthracite	4000K	15°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Anthracite	4000K	24°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Anthracite	4000K	38°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Anthracite	4000K	50°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome	2700K	15°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome	2700K	24°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome	2700K	38°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome	2700K	50°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome	3000K	15°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome	3000K	24°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome	3000K	38°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome	3000K	50°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome	3500K	15°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome	3500K	24°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome	3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≤2 SDCM	50,000 hours	5 years	Remote	



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome		3500K	50°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome		4000K	15°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome		4000K	24°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome		4000K	38°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Chrome		4000K	50°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Custom		2700K	15°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Custom		2700K	24°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Custom		2700K	38°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Custom		2700K	50°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Custom		3000K	15°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Custom		3000K	24°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Custom		3000K	38°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Custom		3000K	50°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Custom		3500K	15°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White Custom		3500K	24°	Aluminium	IP20	<19		3570lm >92+	≥2 SDCM	50,000 hours	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Custom	3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Custom	3500K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Custom	4000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Custom	4000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Custom	4000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Custom	4000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	2700K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	2700K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	2700K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	2700K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	3000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	3000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	3000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	3000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	3500K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	3500K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	3500K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	4000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	4000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	4000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Black	4000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	2700K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	2700K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	2700K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	2700K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	3000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	3000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	3000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	3000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	3500K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	3500K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	3500K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	4000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	4000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	4000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte Silver	4000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	2700K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	2700K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	2700K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	2700K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	3000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	3000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	3000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	3000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	3500K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	3500K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	3500K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	3500K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	4000K	15°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	4000K	24°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	4000K	38°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote
	MODO.AGTFR165	Plaster Recessed	42W	240V	Ø147mm x (H) 184mm	Ø148mm	White	Matte White	4000K	50°	Aluminium	IP20	<19	3570lm	>92+	≥2 SDCM	50,000 hours	5 years	Remote