

LS

MODULO DEEP RECESSED 165

MODULO DR165.....

Collections, Luminaires Type, Modulo, Recessed



Mounting	Recessed
Wattage	42W
Voltage	240V
Dimensions	(D) Ø165mm x (H) 202mm
Cut Out Dimensions	(D) Ø150mm
Finish	Black, White
CCT	2700K, 3000K, 3500K, 4000K
Beam Angle	15°, 24°, 38°, 55°
Material	Aluminium
Driver	Remote
IP Rating	IP44
UGR	<19
Luminous Flux	3570lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Accessories	Honeycomb Lense, Soft Lense
Control Gear	DALI, TRIAC
Warranty	5 years
Luminaires Type	Recessed
Luminous Flux lm	3001+lm

Control Gear

Accessories
Honeycomb Lense, Soft Lense

MODO.DR165						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	2700K	15°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	2700K	24°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	2700K	38°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	2700K	55°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	3000K	15°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	3000K	24°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	3000K	38°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	3000K	55°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	3500K	15°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	3500K	24°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	3500K	38°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	3500K	55°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	4000K	15°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	4000K	24°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	4000K	38°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	Black	4000K	55°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MOD0.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	2700K	15°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	2700K	24°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	2700K	38°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	2700K	55°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	3000K	15°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	3000K	24°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	3000K	38°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	3000K	55°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	3500K	15°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	3500K	24°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	3500K	38°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	3500K	55°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	4000K	15°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	4000K	24°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.DR165	Recessed	42W	240V	(D) Ø165mm x (H) 202mm	(D) Ø150mm	White	4000K	38°	Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed



Image



SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
MODO.DR165	Recessed	42W	240V	(D) 165mm x (H) 202mm	(D) 150mm	White	4000K 55°		Aluminium	Remote	IP44	<19	3570lm	>92+	<2 SDCM	50 000 hours	5 years	Recessed