

LS MODO SPOT LIGHT ONE R110

Collections, Luminaires Type, Modò, Recessed



Mounting	<u>Recessed</u>
Wattage	<u>24W</u>
Voltage	<u>240V</u>
Dimensions	(D) <u>Ø110mm</u> x (H) <u>116mm</u>
Cut Out Dimensions	(D) <u>Ø95mm</u>
Finish	<u>Black, White</u>
CCT	<u>2700K, 3000K, 3500K, 4000K</u>
Beam Angle	<u>15°, 24°, 38°, 55°</u>
Material	<u>Aluminium</u>
Driver	<u>Remote</u>
IP Rating	<u>IP20</u>
UGR	<u><19</u>
Luminous Flux	<u>2040lm</u>
CRI	<u>>92+</u>
Colour Deviation	<u><2 SDCM</u>
Lifetime	<u>50,000 hours</u>
Control Gear	<u>DALI, Phase-Cut</u>
Warranty	<u>5 years</u>
Luminaires Type	<u>Recessed</u>
Luminous Flux lm	<u>2001-2500lm</u>

Control Gear

Accessories

MODO.SLRO110						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	MODO.SLRO110	Recessed	24W	240V	(D) Ø110mm x (H) 116mm	(D) Ø95mm	Black	2700K	15°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	(D) Ø110mm x (H) 116mm	(D) Ø95mm	Black	2700K	24°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	(D) Ø110mm x (H) 116mm	(D) Ø95mm	Black	2700K	38°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	2700K	55°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	3000K	15°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	3000K	24°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	3000K	38°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	3000K	55°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	3500K	15°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	3500K	24°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	3500K	38°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	3500K	55°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	4000K	15°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	4000K	24°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	4000K	38°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	Black	4000K	55°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	2700K	15°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	2700K	24°	Aluminium	IP20	<19	2040lm	>92+	≤2 SDCM	50,000 Hours	5 years	Recessed Remote	



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	2700K	38°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	2700K	55°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	3000K	15°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	3000K	24°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	3000K	38°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	3000K	55°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	3500K	15°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	3500K	24°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	3500K	38°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	3500K	55°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	4000K	15°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	4000K	24°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	4000K	38°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	
	MODO.SLRO110	Recessed	24W	240V	Ø110mm x (H) 116mm	(D) Ø95mm	White	4000K	55°	Aluminium	IP20	<19	2040lm	>92+	≥2 SDCM	50,000 Hours	5 years	Recessed Remote	