

LS

MODOSLO5110.....

MODOSPOTLIGHT ONE S110

Collections, Luminaires Type, Modo, Recessed



Mounting	Recessed
Wattage	24W
Voltage	240V
Dimensions	(W) 110mm x (H) 116mm x (L) 110mm
Cut Out Dimensions	(W) 95mm x (L) 95mm
Finish	Black, White
CCT	2700K, 3000K, 3500K, 4000K
Beam Angle	15°, 24°, 38°, 55°
Material	Aluminium
Driver	Remote
IP Rating	IP20
UGR	<19
Luminous Flux	2040lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Control Gear	DALI, TRIAC
Warranty	5 years
Luminaires Type	Recessed
Luminous Flux lm	2001-2500lm

Control Gear

Accessories

MODOSLOS110						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	MODOSLOS110	Recessed	24W	240V	(W) 110mm x (H) 116mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	2700K	15°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODOSLOS110	Recessed	24W	240V	(W) 110mm x (H) 116mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	2700K	24°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODOSLOS110	Recessed	24W	240V	(W) 110mm x (H) 116mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	2700K	38°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	2700K	55°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	3000K	15°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	3000K	24°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	3000K	38°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	3000K	55°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	3500K	15°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	3500K	24°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	3500K	38°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	3500K	55°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	4000K	15°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	4000K	24°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	4000K	38°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	Black	4000K	55°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	2700K	15°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	2700K	24°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	2700K	38°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	2700K	55°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	3000K	15°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	3000K	24°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	3000K	38°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	3000K	55°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	3500K	15°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	3500K	24°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	3500K	38°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	3500K	55°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	4000K	15°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	4000K	24°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	MODO.SLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm x (L) 110mm	(W) 95mm x (L) 95mm	White	4000K	38°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed



Image



SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
MODOSLOS110	Recessed	24W	240V	(W) 110mm x (H) 118mm (L) 110mm	(W) 95mm x (L) 95mm	White	4000K	55°	Aluminium	Remote	IP20	<19	2040lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed