# MODO SPOT LIGHT ONE S90

MODO.SLOS90.....

Collections, Luminaires Type, Modo, Recessed






| | |
|---|---|
| **Mounting** | Recessed |
| **Wattage** | 15W, 9W |
| **Voltage** | 240V |
| **Dimensions** | (W) 90mm x (L) 90mm x (H) 71mm, (W) 90mm x (L) 90mm x (H) 94mm |
| **Cut Out Dimensions** | (W) 80mm x (L) 80mm |
| **Finish** | Black, White |
| **CCT** | 2700K, 3000K, 3500K, 4000K |
| **Beam Angle** | 15°, 24°, 38°, 55° |
| **Material** | Aluminium |
| **Driver** | Remote |
| **IP Rating** | IP20 |
| **UGR** | <19 |
| **Luminous Flux** | 1275lm, 765lm |
| **CRI** | >92+ |
| **Colour Deviation** | <2 SDCM |
| **Lifetime** | 50,000 hours |
| **Accessories** | Clear Filter, Frosted Filter, Vertical Filter, Woven Filter |
| **Control Gear** | DALI, TRIAC |
| **Warranty** | 5 years |
| **Luminaires Type** | Recessed |
| **Luminous Flux lm** | 1001-1500lm, 501-1000lm |


Control Gear


Accessories


Clear Filter, Frosted Filter, Vertical Filter, Woven Filter








# VARIATIONS

| Image | SKU | Mounting | Wattage | Voltage | Dimensions | Cut Out Dimensions | Finish | CCT | Beam Angle | Material | Driver | IP Rating | UGR | Luminous Flux | CRI | Colour Deviation | Lifetime | Warranty | Luminaires Type |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 2700K | 15° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 2700K | 24° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 2700K | 38° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |

| Image | SKU | Mounting | Wattage | Voltage | Dimensions | Cut Out Dimensions | Finish | CCT | Beam Angle | Material | Driver | IP Rating | UGR | Luminous Flux | CRI | Colour Deviation | Lifetime | Warranty | Luminaires Type |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 2700K | 55° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 3000K | 15° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 3000K | 24° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 3000K | 38° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 3000K | 55° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 4000K | 55° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 3500K | 15° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 2700K | 15° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 2700K | 24° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 3500K | 24° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 2700K | 38° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 3500K | 38° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 3000K | 15° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 3000K | 24° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |

| Image | SKU | Mounting | Wattage | Voltage | Dimensions | Cut Out Dimensions | Finish | CCT | Beam Angle | Material | Driver | IP Rating | UGR | Luminous Flux | CRI | Colour Deviation | Lifetime | Warranty | Luminaires Type |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 3500K | 55° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 2700K | 55° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 3000K | 38° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 3000K | 55° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 4000K | 15° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 3500K | 15° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 3500K | 24° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 4000K | 24° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 3500K | 38° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 3500K | 55° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | Black | 4000K | 38° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 4000K | 15° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 4000K | 24° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 4000K | 38° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |

| Image | SKU | Mounting | Wattage | Voltage | Dimensions | Cut Out Dimensions | Finish | CCT | Beam Angle | Material | Driver | IP Rating | UGR | Luminous Flux | CRI | Colour Deviation | Lifetime | Warranty | Luminaires Type |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
|  | MODO.SLOS90 | Recessed | 15W | 240V | (W) 90mm x (L) 90mm x (H) 94mm | (W) 80mm x (L) 80mm | White | 4000K | 55° | Aluminium | Remote | IP20 | <19 | 1275lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 2700K | 15° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 2700K | 24° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 2700K | 38° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 2700K | 55° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 3000K | 15° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 3000K | 24° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 3000K | 38° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 3000K | 55° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 3500K | 15° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 3500K | 24° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 3500K | 38° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 3500K | 55° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 4000K | 15° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |

| Image | SKU | Mounting | Wattage | Voltage | Dimensions | Cut Out Dimensions | Finish | CCT | Beam Angle | Material | Driver | IP Rating | UGR | Luminous Flux | CRI | Colour Deviation | Lifetime | Warranty | Luminaires Type |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 4000K | 24° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 4000K | 38° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | Black | 4000K | 55° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 2700K | 15° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 2700K | 24° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 2700K | 38° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 2700K | 55° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 3000K | 15° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 3000K | 24° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 3000K | 38° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 3000K | 55° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 3500K | 15° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 3500K | 24° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 3500K | 38° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |

| Image | SKU | Mounting | Wattage | Voltage | Dimensions | Cut Out Dimensions | Finish | CCT | Beam Angle | Material | Driver | IP Rating | UGR | Luminous Flux | CRI | Colour Deviation | Lifetime | Warranty | Luminaires Type |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 3500K | 55° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 4000K | 15° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 4000K | 24° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 4000K | 38° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |
|  | MODO.SLOS90 | Recessed | 9W | 240V | (W) 90mm x (L) 90mm x (H) 71mm | (W) 80mm x (L) 80mm | White | 4000K | 55° | Aluminium | Remote | IP20 | <19 | 765lm | >92+ | <2 SDCM | 50,000 hours | 5 years | Recessed |