



Wattage	10W/m
Voltage	DC24V
Dimensions	(W) 6mm x (H) 12mm
Cut Length	50mm
CCT	2700K, 3000K, 3500K, 4000K, 5000K, RGB, RGBW, Solid Colours
Beam Angle	160°
Driver	Remote
IP Rating	IP67
Luminaires Type	Linear Systems – Linear Light Source
Luminous Flux	360lm
CRI	>92+, >98
Colour Deviation	<3 SDCM
Accessories	Bottom Power End Cap, End Cap, Front Power End Cap, Mounting Profile, Side Power End Cap, Surface Mounting Clip, Curved Profile
Control Gear	1-10V, DALI, DMX, Non-dimmable, Phase-Cut, RGB Controller, RGBW Controller
Warranty	5 years
Luminous Flux lm	1-500lm

Control Gear

Accessories

Bottom Power End Cap, End Cap, Front Power End Cap, Mounting Profile, Side Power End Cap, Surface Mounting Clip, Curved Profile

NEON.M0612						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS






Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminaires Type	Luminous Flux	CRI	Colour Deviation	Warranty
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	2700K	160°	IP67	Linear Systems - Linear Light Source	360lm	>92+	≤3 SDCM	5 years	Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	2700K	160°	IP67	Linear Systems - Linear Light Source	360lm	>98	≤3 SDCM	5 years	Remote



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminaires Type	Luminous Flux	CRI	Colour Deviation	Warranty
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	3000K	160°	IP67	Linear Systems - Linear Light Source	360lm	>92+	≤3 SDCM	5 years	Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	3000K	160°	IP67	Linear Systems - Linear Light Source	360lm	>98	≤3 SDCM	5 years	Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	3500K	160°	IP67	Linear Systems - Linear Light Source	150lm	>92+	≤3 SDCM	5 years	Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	3500K	160°	IP67	Linear Systems - Linear Light Source	150lm	>98	≤3 SDCM	5 years	Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	4000K	160°	IP67	Linear Systems - Linear Light Source	150lm	>92+	≤3 SDCM	5 years	Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	4000K	160°	IP67	Linear Systems - Linear Light Source	360lm	>98	≤3 SDCM	5 years	Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	5000K	160°	IP67	Linear Systems - Linear Light Source	360lm	>92+	≤3 SDCM	5 years	Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	5000K	160°	IP67	Linear Systems - Linear Light Source	360lm	>98	≤3 SDCM	5 years	Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	RGB	160°	IP67	Linear Systems - Linear Light Source	360lm	>92+	≤3 SDCM	5 years	Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	RGB	160°	IP67	Linear Systems - Linear Light Source	360lm	>98	≤3 SDCM	5 years	Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	RGBW	160°	IP67	Linear Systems - Linear Light Source	360lm	>92+	≤3 SDCM	5 years	Remote



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminaires Type	Luminous Flux	CRI	Colour Deviation	Warranty
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	RGBW	160°	IP67		Linear Systems - Linear Light Source	360lm	>98	≤3 SDCM	5 years Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	Solid Colours	160°	IP67		Linear Systems - Linear Light Source	360lm	>92+	≤3 SDCM	5 years Remote
	NEON.M0612	10W/m	DC24V	(W) 6mm x (H) 12mm	50mm	Solid Colours	160°	IP67		Linear Systems - Linear Light Source	360lm	>98	≤3 SDCM	5 years Remote