

Wattage	15W/m
Voltage	DC24V
Dimensions	(W) 16mm x (H) 15mm
Cut Length	50mm
CCT	2700K, 3000K, 3500K, 4000K, 5000K, RGB, RGBW, Solid Colours
Beam Angle	160°
Driver	Remote
IP Rating	IP67
Luminous Flux	960lm/m
CRI	>92+, >98
Colour Deviation	<3 SDCM
Accessories	Bottom Power End Cap, End Caps, Front Power End Cap, Mounting Profile, Side Power End Cap, Surface Mounting Clip, Aluminum Clips, Injection Bottom Cable Endcap, Injection Direct Cable Endcap, Injection Side Cable Endcap
Control Gear	1-10V, DALI, DMX, Non-dimmable, Phase-Cut, RGB Controller, RGBW Controller
Warranty	5 years
Luminaires Type	Linear Systems - Linear Light Source
Luminous Flux lm	501-1000lm

Control Gear

Accessories

Bottom Power End Cap, End Caps, Front Power End Cap, Mounting Profile, Side Power End Cap, Surface Mounting Clip, Aluminum Clips, Injection Bottom Cable Endcap, Injection Direct Cable Endcap, Injection Side Cable Endcap

NEON.PT1615							
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR	



VARIATIONS

Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Warranty	Luminaires Type
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	2700K	160°	IP67	960lm/m	>92+	<3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	2700K	160°	IP67	960lm/m	>98	<3 SDCM	5 years	Linear Systems - Linear Light Source	Remote



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Warranty	Luminaires Type
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	3000K	160°	IP67	960lm/m	>92+	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	3000K	160°	IP67	960lm/m	>98	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	3500K	160°	IP67	960lm/m	>92+	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	3500K	160°	IP67	960lm/m	>98	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	4000K	160°	IP67	960lm/m	>92+	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	4000K	160°	IP67	960lm/m	>98	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	5000K	160°	IP67	960lm/m	>92+	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	5000K	160°	IP67	960lm/m	>98	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	RGB	160°	IP67	960lm/m	>92+	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	RGB	160°	IP67	960lm/m	>98	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	RGBW	160°	IP67	960lm/m	>92+	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm x (H) 15mm	50mm	RGBW	160°	IP67	960lm/m	>98	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote



Image	SKU	Wattage	Voltage	Dimensions	Cut Length	CCT	Beam Angle	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Warranty	Luminaires Type
	NEON.PT1615	15W/m	DC24V	(W) 16mm (H) 13mm	50mm	Solid Colours	160°	IP67	960lm/m	>92+	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote
	NEON.PT1615	15W/m	DC24V	(W) 16mm (H) 13mm	50mm	Solid Colours	160°	IP67	960lm/m	>98	≥3 SDCM	5 years	Linear Systems - Linear Light Source	Remote