



Mounting	Spike, Surface, Tree Mounted
Wattage	5W
Voltage	DC24V
Dimensions	(D) Ø45mm x (L) 90mm x (H) 290mm
Finish	Black
CCT	3000K, 4000K
IP Rating	IP66
IK Rating	IK04
Luminous Flux	365lm
CRI	>83+
Colour Deviation	<3 SDCM
Lifetime	50,000 hours
Control Gear	1-10V, DALI, Non-dimmable
Accessories	Garden Spike, Tree Mount Strap, Surface Mount
Beam Angle	10°60°, 15°, 20°30°, 25°, 40°, 56°
Driver	Remote
Material	Aluminium
Warranty	5 years
Luminaires Type	Outdoor
Luminous Flux lm	1-500lm

Control Gear

Accessories
Garden Spike, Tree Mount Strap, Surface Mount

POINT.SP45						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Wattage	Voltage	Dimensions	Finish	CCT	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Beam Angle	Driver	Material	Warranty	Luminaires Type
	POINT.SP45 5W		DC24V	(D) Ø45mm x (L) 90mm (H) 290mm	Black	3000K	IP66	IK04	365lm	>83+ <3	SDCM	50,000 hours	10°60°	Remote	Aluminium	5 years	Outdoor
	POINT.SP45 5W		DC24V	(D) Ø45mm x (L) 90mm (H) 290mm	Black	3000K	IP66	IK04	365lm	>83+ <3	SDCM	50,000 hours	15°	Remote	Aluminium	5 years	Outdoor
	POINT.SP45 5W		DC24V	(D) Ø45mm x (L) 90mm (H) 290mm	Black	3000K	IP66	IK04	365lm	>83+ <3	SDCM	50,000 hours	20°30°	Remote	Aluminium	5 years	Outdoor
	POINT.SP45 5W		DC24V	(D) Ø45mm x (L) 90mm (H) 290mm	Black	3000K	IP66	IK04	365lm	>83+ <3	SDCM	50,000 hours	25°	Remote	Aluminium	5 years	Outdoor



Image

SKU Wattage Voltage Dimensions Finish CCT IP Rating IK Rating Luminous Flux CRI Colour Deviation Lifetime Beam Angle Driver Material Warranty Luminaires Type



POINT.SP45 5W DC24V (D) Ø45mm
x (H) 90mm
x (F) 290mm Black 3000K IP66 IK04 365lm >83+ <3 SDCM 50,000 hours 40° Remote Aluminium 5 years Outdoor



POINT.SP45 5W DC24V (D) Ø45mm
x (H) 90mm
x (F) 290mm Black 3000K IP66 IK04 365lm >83+ <3 SDCM 50,000 hours 56° Remote Aluminium 5 years Outdoor



POINT.SP45 5W DC24V (D) Ø45mm
x (H) 90mm
x (F) 290mm Black 4000K IP66 IK04 365lm >83+ <3 SDCM 50,000 hours 10°60° Remote Aluminium 5 years Outdoor



POINT.SP45 5W DC24V (D) Ø45mm
x (H) 90mm
x (F) 290mm Black 4000K IP66 IK04 365lm >83+ <3 SDCM 50,000 hours 15° Remote Aluminium 5 years Outdoor



POINT.SP45 5W DC24V (D) Ø45mm
x (H) 90mm
x (F) 290mm Black 4000K IP66 IK04 365lm >83+ <3 SDCM 50,000 hours 20°30° Remote Aluminium 5 years Outdoor



POINT.SP45 5W DC24V (D) Ø45mm
x (H) 90mm
x (F) 290mm Black 4000K IP66 IK04 365lm >83+ <3 SDCM 50,000 hours 25° Remote Aluminium 5 years Outdoor



POINT.SP45 5W DC24V (D) Ø45mm
x (H) 90mm
x (F) 290mm Black 4000K IP66 IK04 365lm >83+ <3 SDCM 50,000 hours 40° Remote Aluminium 5 years Outdoor



POINT.SP45 5W DC24V (D) Ø45mm
x (H) 90mm
x (F) 290mm Black 4000K IP66 IK04 365lm >83+ <3 SDCM 50,000 hours 56° Remote Aluminium 5 years Outdoor