



|                  |                                    |
|------------------|------------------------------------|
| Mounting         | Spike, Surface, Tree Mounted       |
| Wattage          | 15W                                |
| Voltage          | DC24V                              |
| Dimensions       | (D) Ø75mm x (L) 135mm x (H) 331mm  |
| Finish           | Black                              |
| CCT              | 3000K, 4000K                       |
| Beam Angle       | 10°60°, 15°, 20°30°, 25°, 40°, 56° |
| Material         | Aluminium                          |
| Driver           | Remote                             |
| IP Rating        | IP68                               |
| IK Rating        | IK04                               |
| Luminous Flux    | 2000lm                             |
| CRI              | >83+                               |
| Colour Deviation | <3 SDCM                            |
| Lifetime         | 50,000 hours                       |
| Control Gear     | 1-10V, DALI, Non-dimmable          |
| Accessories      | Garden Spike                       |
| Warranty         | 5 years                            |
| Luminaires Type  | Outdoor                            |
| Luminous Flux lm | 1501-2000lm                        |

Control Gear

Accessories

Garden Spike

|              |         |        |                   |     |            |              |
|--------------|---------|--------|-------------------|-----|------------|--------------|
| POINT.SP75   |         |        |                   |     |            |              |
| PRODUCT NAME | WATTAGE | FINISH | INNER TRIM FINISH | CCT | BEAM ANGLE | CONTROL GEAR |

VARIATIONS

| Image | SKU              | Mounting | Wattage | Voltage | Dimensions                        | Finish | CCT   | Beam Angle | Material  | Driver | IP Rating | IK Rating | Luminous Flux | CRI  | Colour Deviation | Lifetime     | Warranty | Luminaires Type |
|-------|------------------|----------|---------|---------|-----------------------------------|--------|-------|------------|-----------|--------|-----------|-----------|---------------|------|------------------|--------------|----------|-----------------|
|       | POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm x (L) 135mm x (H) 331mm | Black  | 3000K | 10°60°     | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |
|       | POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm x (L) 135mm x (H) 331mm | Black  | 3000K | 15°        | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |
|       | POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm x (L) 135mm x (H) 331mm | Black  | 3000K | 20°30°     | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |
|       | POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm x (L) 135mm x (H) 331mm | Black  | 3000K | 25°        | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |



Image



| SKU              | Mounting | Wattage | Voltage | Dimensions                            | Finish | CCT   | Beam Angle | Material  | Driver | IP Rating | IK Rating | Luminous Flux | CRI  | Colour Deviation | Lifetime     | Warranty | Luminaires Type |
|------------------|----------|---------|---------|---------------------------------------|--------|-------|------------|-----------|--------|-----------|-----------|---------------|------|------------------|--------------|----------|-----------------|
| POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm<br>(L) 135mm x<br>(H) 331mm | Black  | 3000K | 40°        | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |
| POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm<br>(L) 135mm x<br>(H) 331mm | Black  | 3000K | 56°        | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |
| POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm<br>(L) 135mm x<br>(H) 331mm | Black  | 4000K | 10°/60°    | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |
| POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm<br>(L) 135mm x<br>(H) 331mm | Black  | 4000K | 15°        | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |
| POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm<br>(L) 135mm x<br>(H) 331mm | Black  | 4000K | 20°/30°    | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |
| POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm<br>(L) 135mm x<br>(H) 331mm | Black  | 4000K | 25°        | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |
| POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm<br>(L) 135mm x<br>(H) 331mm | Black  | 4000K | 40°        | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |
| POINT.SP75 Spike |          | 15W     | DC24V   | (D) Ø75mm<br>(L) 135mm x<br>(H) 331mm | Black  | 4000K | 56°        | Aluminium | Remote | IP68      | IK04      | 2000lm        | >83+ | <3 SDCM          | 50,000 hours | 5 years  | Outdoor         |

