



Mounting	Rail
Wattage	1.5W
Voltage	DC24V
Dimensions	(W) 17.5mm x (H) 21mm x (L) 185mm
Suitable Locations	30 x 30mm square handrail with 0.8-3mm wall thickness
Finish	Stainless Steel
CCT	3000K, 4000K
Beam Angle	Symmetric
Material	Stainless Steel
IP Rating	IP67
Luminous Flux	140lm
CRI	>83+
Colour Deviation	<3 SDCM
Lifetime	50,000 hours
Control Gear	1-10V, DALI, Non-dimmable
Warranty	5 years
Luminaires Type	Outdoor
Luminous Flux lm	1-500lm

Control Gear

Accessories

RALFL185						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Suitable Locations	Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	RALFL185 Rail		1.5W	DC24V	(W) 17.5mm x (H) 21mm x (L) 185mm	30 x 30mm square handrail with 0.8-3mm wall thickness	Stainless Steel	3000K	Symmetric	Stainless Steel	IP67	140lm	>83+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
	RALFL185 Rail		1.5W	DC24V	(W) 17.5mm x (H) 21mm x (L) 185mm	Any Suitable Locations	Stainless Steel	3000K	Symmetric	Stainless Steel	IP67	140lm	>83+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
	RALFL185 Rail		1.5W	DC24V	(W) 17.5mm x (H) 21mm x (L) 185mm	30 x 30mm square handrail with 0.8-3mm wall thickness	Stainless Steel	3000K	Symmetric	Stainless Steel	IP67	140lm	>83+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Suitable Locations	Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
RAL.FL185	Rail	1.5W	DC24V	W: 165mm x H: 21mm x D: 185mm	30 x 30mm square handrail with 0.8-3mm wall thickness	Stainless Steel	4000K	Symmetric	Stainless Steel	IP67	140lm	>83+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
RAL.FL185	Rail	1.5W	DC24V	W: 165mm x H: 21mm x D: 185mm	30 x 30mm square handrail with 0.8-3mm wall thickness	Stainless Steel	4000K	Symmetric	Stainless Steel	IP67	140lm	>83+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
RAL.FL185	Rail	1.5W	DC24V	W: 165mm x H: 21mm x D: 185mm	30 x 30mm square handrail with 0.8-3mm wall thickness	Stainless Steel	4000K	Symmetric	Stainless Steel	IP67	140lm	>83+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor