

Luminaires Type, Outdoor



Control Gear

Accessories

RAL.RL185			[]			
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	ССТ	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Suitable Locations	Finish	сст	Beam Angle	Material I	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
	RAL.RL185	Rail	1.5W	DC24V	(W). 17.5mm x (H) 21mm 185mm	Any Suitable Locations	Stainless Steel	3000K	Symmetric	Stainless Steel	P67	140lm	>83+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
-	RAL.RL185	Rail	1.5W	DC24V	(W) _{5mm x} (H) 21mm 185mm	Any Suitable Locations	Stainless Steel	3000K	Symmetric	Stainless _I Steel	P67	140lm	>83+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
-	RAL.RL185	Rail	1.5W	DC24V	(¥)) _{5mm} x (H) 21mm 185mm	Any Suitable Locations	Stainless Steel	3000K	Symmetric	Stainless I Steel	P67	140lm	>83+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor



ſ	Image	SKU	Mounting	y Wattage	Voltage	Dimensions	Suitable Locations	Finish	сст	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Control Gear	Warranty	Luminaires Type
y h. ////		RAL.RL18	5 Rail	1.5W	DC24V	(¥)) _{5mm x} (H) 21mm ¥ (L) 185mm	Any Suitable Locations	Stainless Steel	4000K	Symmetric	Stainless Steel	IP67	140lm	>83+	<3 SDCM	50,000 hours	1-10V	5 years	Outdoor
		RAL.RL18	5 Rail	1.5W	DC24V	(W) ₅ mm x (H) 21mm 185mm	Any Suitable Locations	Stainless Steel	4000K	Symmetric	Stainless Steel	IP67	140lm	>83+	<3 SDCM	50,000 hours	DALI	5 years	Outdoor
		RAL.RL18	5 Rail	1.5W	DC24V	(W) 175mm x (H) 21mm 185mm	Any Suitable Locations	Stainless Steel	4000K	Symmetric	Stainless Steel	IP67	140lm	>83+	<3 SDCM	50,000 hours	Non-dimmable	5 years	Outdoor