



Mounting	Suspended
Wattage	9W
Voltage	240V
Dimensions	(D) Ø100mm
Length	1000mm, 1200mm, 220mm, 400mm, 600mm, 800mm
Finish	Black, Brass, Copper, Custom, White
CCT	3000K, 4000K
Beam Angle	60°
Material	Aluminium, Brass, Copper
IP Rating	IP20
Luminous Flux	650lm
CRI	>83+
Colour Deviation	<3 SDCM
Lifetime	45,000 hours
Accessories	GU10 Globe
Control Gear	TRIAC
Warranty	5 years
Luminaires Type	Suspended
Luminous Flux lm	501-1000lm

Control Gear

Accessories
GU10 Globe

REA.SP100						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Length	Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1000mm	Black	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1000mm	Black	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Length	Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1000mm	Brass	3000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1000mm	Brass	4000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1000mm	Copper	3000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1200mm	Copper	4000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1000mm	Copper	4000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1200mm	Custom	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1000mm	Custom	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1200mm	Custom	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1200mm	White	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1200mm	White	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1000mm	Custom	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	220mm	Black	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Length	Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	220mm	Black	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1000mm	White	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1000mm	White	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	220mm	Brass	3000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	220mm	Brass	4000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1200mm	Black	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	220mm	Copper	3000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	220mm	Copper	4000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	220mm	Custom	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	220mm	Custom	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1200mm	Black	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	220mm	White	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Length	Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
REA.SP100	Suspended	9W	240V	(D) Ø100mm	220mm	White	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
REA.SP100	Suspended	9W	240V	(D) Ø100mm	400mm	Black	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
REA.SP100	Suspended	9W	240V	(D) Ø100mm	400mm	Brass	4000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
REA.SP100	Suspended	9W	240V	(D) Ø100mm	400mm	Black	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
REA.SP100	Suspended	9W	240V	(D) Ø100mm	400mm	Brass	3000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
REA.SP100	Suspended	9W	240V	(D) Ø100mm	400mm	Copper	3000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
REA.SP100	Suspended	9W	240V	(D) Ø100mm	400mm	Copper	4000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
REA.SP100	Suspended	9W	240V	(D) Ø100mm	1200mm	Brass	3000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
REA.SP100	Suspended	9W	240V	(D) Ø100mm	400mm	Custom	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
REA.SP100	Suspended	9W	240V	(D) Ø100mm	400mm	Custom	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
REA.SP100	Suspended	9W	240V	(D) Ø100mm	400mm	White	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
REA.SP100	Suspended	9W	240V	(D) Ø100mm	1200mm	Brass	4000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Length	Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	400mm	White	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	600mm	Black	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	600mm	Black	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	600mm	Brass	3000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	1200mm	Copper	3000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	600mm	Brass	4000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	600mm	Copper	3000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	600mm	Copper	4000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	600mm	Custom	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	600mm	Custom	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	600mm	White	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	600mm	White	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Length	Finish	CCT	Beam Angle	Material	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	800mm	Black	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	800mm	Black	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	800mm	Brass	3000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	800mm	Brass	4000K	60°	Brass	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	800mm	Copper	3000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	800mm	Copper	4000K	60°	Copper	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	800mm	Custom	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	800mm	Custom	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	800mm	White	3000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years
	REA.SP100	Suspended	9W	240V	(D) Ø100mm	800mm	White	4000K	60°	Aluminium	IP20	650lm	>83+	<3 SDCM	45,000 hours	5 years