



Mounting	Track 3-Circuit
Wattage	25W
Voltage	240V
Dimensions	(D) Ø106mm x (L) 85mm
Finish	Black, White
Inner Trim Finish	Black, White
CCT	2700K, 3000K, 4000K, 5000K
Beam Angle	15°, 24°, 36°, 60°
Material	Aluminium
Driver	Remote
IP Rating	IP20
Luminous Flux	2039lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Control Gear	DALI, Phase-Cut
Warranty	5 years
Luminaires Type	Track Mounted – Track Luminaires
Luminous Flux lm	2001-2500lm

Control Gear

Accessories

SAI.S106						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.S106	Track 3-Circuit	25W	240V	(D) Ø106mm x (L) 85mm	Black	Black	2700K	15°	Aluminium	IP20	2039lm	>92+	<2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) Ø106mm x (L) 85mm	Black	Black	2700K	24°	Aluminium	IP20	2039lm	>92+	<2 SDCM	50,000 hours	Remote



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	2700K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	2700K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	3000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	3000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	3000K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	3000K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	4000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	4000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	4000K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	4000K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	5000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	5000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote





Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	5000K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	Black	5000K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	2700K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	2700K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	2700K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	2700K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	3000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	3000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	3000K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	3000K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	4000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
	SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	4000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote



Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	4000K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	4000K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	5000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	5000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	5000K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	Black	White	5000K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	2700K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	2700K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	2700K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	2700K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	3000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	3000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote





Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	3000K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	3000K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	4000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	4000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	4000K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	4000K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	5000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	5000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	5000K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	Black	5000K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	2700K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	2700K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote





Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	2700K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	2700K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	3000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	3000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	3000K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	3000K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	4000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	4000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	4000K	36°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	4000K	60°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	5000K	15°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote
SAI.S106	Track 3-Circuit	25W	240V	(D) 106mm x (L) 85mm	White	White	5000K	24°	Aluminium	IP20	2039lm	>92+	≤2 SDCM	50,000 hours	Remote





Image

SKU	Mounting	Wattage	Voltage	Dimensions	Finish	Inner Trim Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
SAI.S106	Track 3- Circuit	25W	240V	(D) Ø106mm x (L) 85mm	White	White	5000K	36°	Aluminium	IP20	2039lm	>92+	≥2 SDCM	50,000 hours	Remote
SAI.S106	Track 3- Circuit	25W	240V	(D) Ø106mm x (L) 85mm	White	White	5000K	60°	Aluminium	IP20	2039lm	>92+	≥2 SDCM	50,000 hours	Remote

