





| | |
|--------------------------|----------------------------------|
| Mounting | Track 3-Circuit |
| Wattage | 25W |
| Voltage | 240V |
| Dimensions | (D) Ø106mm x (L) 85mm |
| Finish | Black, White |
| Inner Trim Finish | Black, White |
| CCT | 2700K, 3000K, 4000K, 5000K |
| Beam Angle | 15°, 24°, 36°, 60° |
| Material | Aluminium |
| Driver | Remote |
| IP Rating | IP20 |
| Luminous Flux | 2039lm |
| CRI | >92+ |
| Colour Deviation | <2 SDCM |
| Lifetime | 50,000 hours |
| Control Gear | DALI, Phase-Cut |
| Warranty | 5 years |
| Luminaires Type | Track Mounted – Track Luminaires |
| Luminous Flux lm | 2001-2500lm |

Control Gear

Accessories

| | | | | | | |
|--------------|---------|--------|-------------------|-----|------------|--------------|
| SAI.S106 | | | | | | |
| PRODUCT NAME | WATTAGE | FINISH | INNER TRIM FINISH | CCT | BEAM ANGLE | CONTROL GEAR |

VARIATIONS

| Image | SKU | Mounting | Wattage | Voltage | Dimensions | Finish | Inner Trim Finish | CCT | Beam Angle | Material | Driver | IP Rating | Luminous Flux | CRI | Colour Deviation | Lifetime |
|---|----------|-----------------|---------|---------|-----------------------|--------|-------------------|-------|------------|-----------|--------|-----------|---------------|---------|------------------|----------|
|  | SAI.S106 | Track 3-Circuit | 25W | 240V | (D) Ø106mm x (L) 85mm | Black | Black | 2700K | 15° | Aluminium | IP20 | 2039lm | >92+ | <2 SDCM | 50,000 hours | Remote |
|  | SAI.S106 | Track 3-Circuit | 25W | 240V | (D) Ø106mm x (L) 85mm | Black | Black | 2700K | 24° | Aluminium | IP20 | 2039lm | >92+ | <2 SDCM | 50,000 hours | Remote |



Image

| SKU | Mounting | Wattage | Voltage | Dimensions | Finish | Inner Trim Finish | CCT | Beam Angle | Material | Driver | IP Rating | Luminous Flux | CRI | Colour Deviation | Lifetime |
|----------|-----------------|---------|---------|----------------------|--------|-------------------|-------|------------|-----------|--------|-----------|---------------|---------|------------------|----------|
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 2700K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 2700K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 3000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 3000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 3000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 3000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 4000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 4000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 4000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 4000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 5000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 5000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |





Image

| SKU | Mounting | Wattage | Voltage | Dimensions | Finish | Inner Trim Finish | CCT | Beam Angle | Material | Driver | IP Rating | Luminous Flux | CRI | Colour Deviation | Lifetime |
|----------|-----------------|---------|---------|----------------------|--------|-------------------|-------|------------|-----------|--------|-----------|---------------|---------|------------------|----------|
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 5000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | Black | 5000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 2700K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 2700K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 2700K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 2700K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 3000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 3000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 3000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 3000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 4000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 4000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |





Image

| SKU | Mounting | Wattage | Voltage | Dimensions | Finish | Inner Trim Finish | CCT | Beam Angle | Material | Driver | IP Rating | Luminous Flux | CRI | Colour Deviation | Lifetime |
|----------|-----------------|---------|---------|----------------------|--------|-------------------|-------|------------|-----------|--------|-----------|---------------|---------|------------------|----------|
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 4000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 4000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 5000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 5000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 5000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | Black | White | 5000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 2700K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 2700K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 2700K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 2700K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 3000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 3000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |





Image

| SKU | Mounting | Wattage | Voltage | Dimensions | Finish | Inner Trim Finish | CCT | Beam Angle | Material | Driver | IP Rating | Luminous Flux | CRI | Colour Deviation | Lifetime |
|----------|-----------------|---------|---------|----------------------|--------|-------------------|-------|------------|-----------|--------|-----------|---------------|---------|------------------|----------|
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 3000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 3000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 4000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 4000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 4000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 4000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 5000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 5000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 5000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | Black | 5000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 2700K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 2700K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |





Image

| SKU | Mounting | Wattage | Voltage | Dimensions | Finish | Inner Trim Finish | CCT | Beam Angle | Material | Driver | IP Rating | Luminous Flux | CRI | Colour Deviation | Lifetime |
|----------|-----------------|---------|---------|----------------------|--------|-------------------|-------|------------|-----------|--------|-----------|---------------|---------|------------------|----------|
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 2700K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 2700K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 3000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 3000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 3000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 3000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 4000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 4000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 4000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 4000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 5000K | 15° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3-Circuit | 25W | 240V | (D) 106mm x (L) 85mm | White | White | 5000K | 24° | Aluminium | IP20 | 2039lm | >92+ | ≤2 SDCM | 50,000 hours | Remote |





Image

| SKU | Mounting | Wattage | Voltage | Dimensions | Finish | Inner Trim Finish | CCT | Beam Angle | Material | Driver | IP Rating | Luminous Flux | CRI | Colour Deviation | Lifetime |
|----------|---------------------|---------|---------|-----------------------------|--------|-------------------------|-------|---------------|-----------|--------|--------------|------------------|------------|---------------------|----------|
| SAI.S106 | Track 3- Circuit | 25W | 240V | (D) Ø106mm x (L) 85mm | White | White | 5000K | 36° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |
| SAI.S106 | Track 3- Circuit | 25W | 240V | (D) Ø106mm x (L) 85mm | White | White | 5000K | 60° | Aluminium | IP20 | 2039lm | >92+ | ≥2 SDCM | 50,000 hours | Remote |