

<b>Mounting</b>	Track 3-Circuit
<b>Wattage</b>	12W
<b>Voltage</b>	240V
<b>Dimensions</b>	(D) Ø65mm x (L) 64mm
<b>Finish</b>	Black, White
<b>CCT</b>	2700K, 3000K, 4000K, 5000K
<b>Beam Angle</b>	15°, 24°, 36°, 60°
<b>Material</b>	Aluminium
<b>Driver</b>	Remote
<b>IP Rating</b>	IP20
<b>Luminous Flux</b>	1050lm
<b>CRI</b>	>92+
<b>Colour Deviation</b>	<2 SDCM
<b>Lifetime</b>	50,000 hours
<b>Control Gear</b>	DALI, Phase-Cut
<b>Warranty</b>	5 years
<b>Luminaires Type</b>	Track Mounted – Track Luminaires
<b>Luminous Flux lm</b>	1001-1500lm

Control Gear

Accessories

SAI.WW106						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

## VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours




Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours



Image

SKU Mounting Wattage Voltage Dimensions Finish CCT Beam Angle Material Driver IP Rating Luminous Flux CRI Colour Deviation Lifetime



SAI.WW106 Track 3-Circuit 12W 240V (D) Ø65mm x (L) 64mm White 5000K 36° Aluminium Remote IP20 1050lm >92+ <2 SDCM 50,000 hours



SAI.WW106 Track 3-Circuit 12W 240V (D) Ø65mm x (L) 64mm White 5000K 60° Aluminium Remote IP20 1050lm >92+ <2 SDCM 50,000 hours