

Mounting	Track 3-Circuit
Wattage	12W
Voltage	240V
Dimensions	(D) Ø65mm x (L) 64mm
Finish	Black, White
CCT	2700K, 3000K, 4000K, 5000K
Beam Angle	15°, 24°, 36°, 60°
Material	Aluminium
Driver	Remote
IP Rating	IP20
Luminous Flux	1050lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Control Gear	DALI, Phase-Cut
Warranty	5 years
Luminaires Type	Track Mounted – Track Luminaires
Luminous Flux lm	1001-1500lm

Control Gear

Accessories

SAI.WW106						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours




Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	2700K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	3000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours






Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	4000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	Black	5000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	Luminous Flux	CRI	Colour Deviation	Lifetime
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	2700K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	3000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	36°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	4000K	60°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	15°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours
	SAI.WW106	Track 3-Circuit	12W	240V	(D) Ø65mm x (L) 64mm	White	5000K	24°	Aluminium	Remote	IP20	1050lm	>92+	<2 SDCM	50,000 hours



Image

SKU Mounting Wattage Voltage Dimensions Finish CCT Beam Angle Material Driver IP Rating Luminous Flux CRI Colour Deviation Lifetime



SAI.WW106 Track 3-Circuit 12W 240V (D) Ø65mm x (L) 64mm White 5000K 36° Aluminium Remote IP20 1050lm >92+ <2 SDCM 50,000 hours



SAI.WW106 Track 3-Circuit 12W 240V (D) Ø65mm x (L) 64mm White 5000K 60° Aluminium Remote IP20 1050lm >92+ <2 SDCM 50,000 hours