

|                         |                                  |
|-------------------------|----------------------------------|
| <b>Mounting</b>         | Track 3-Circuit                  |
| <b>Wattage</b>          | 12W                              |
| <b>Voltage</b>          | 240V                             |
| <b>Dimensions</b>       | (D) Ø65mm x (L) 64mm             |
| <b>Finish</b>           | Black, White                     |
| <b>CCT</b>              | 2700K, 3000K, 4000K, 5000K       |
| <b>Beam Angle</b>       | 15°, 24°, 36°, 60°               |
| <b>Material</b>         | Aluminium                        |
| <b>Driver</b>           | Remote                           |
| <b>IP Rating</b>        | IP20                             |
| <b>Luminous Flux</b>    | 1050lm                           |
| <b>CRI</b>              | >92+                             |
| <b>Colour Deviation</b> | <2 SDCM                          |
| <b>Lifetime</b>         | 50,000 hours                     |
| <b>Control Gear</b>     | DALI, Phase-Cut                  |
| <b>Warranty</b>         | 5 years                          |
| <b>Luminaires Type</b>  | Track Mounted – Track Luminaires |
| <b>Luminous Flux lm</b> | 1001-1500lm                      |

Control Gear


Accessories

|              |         |        |                   |     |            |              |
|--------------|---------|--------|-------------------|-----|------------|--------------|
| SAI.WW106    |         |        |                   |     |            |              |
| PRODUCT NAME | WATTAGE | FINISH | INNER TRIM FINISH | CCT | BEAM ANGLE | CONTROL GEAR |

## VARIATIONS

| Image | SKU       | Mounting        | Wattage | Voltage | Dimensions           | Finish | CCT   | Beam Angle | Material  | Driver | IP Rating | Luminous Flux | CRI  | Colour Deviation | Lifetime     |
|-------|-----------|-----------------|---------|---------|----------------------|--------|-------|------------|-----------|--------|-----------|---------------|------|------------------|--------------|
|       | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm x (L) 64mm | Black  | 2700K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|       | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm x (L) 64mm | Black  | 2700K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |



| Image   | SKU       | Mounting        | Wattage | Voltage | Dimensions              | Finish | CCT   | Beam Angle | Material  | Driver | IP Rating | Luminous Flux | CRI  | Colour Deviation | Lifetime     |
|---|-----------|-----------------|---------|---------|-------------------------|--------|-------|------------|-----------|--------|-----------|---------------|------|------------------|--------------|
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 2700K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 2700K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 3000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 3000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 3000K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 3000K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 4000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 4000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 4000K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 4000K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 5000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 5000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |



| Image   | SKU       | Mounting        | Wattage | Voltage | Dimensions              | Finish | CCT   | Beam Angle | Material  | Driver | IP Rating | Luminous Flux | CRI  | Colour Deviation | Lifetime     |
|---|-----------|-----------------|---------|---------|-------------------------|--------|-------|------------|-----------|--------|-----------|---------------|------|------------------|--------------|
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 5000K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 5000K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 2700K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 2700K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 2700K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 2700K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 3000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 3000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 3000K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 3000K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 4000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 4000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |



| Image   | SKU       | Mounting        | Wattage | Voltage | Dimensions              | Finish | CCT   | Beam Angle | Material  | Driver | IP Rating | Luminous Flux | CRI  | Colour Deviation | Lifetime     |
|---|-----------|-----------------|---------|---------|-------------------------|--------|-------|------------|-----------|--------|-----------|---------------|------|------------------|--------------|
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 4000K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 4000K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 5000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 5000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 5000K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | Black  | 5000K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 2700K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 2700K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 2700K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 2700K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 3000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 3000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |



| Image   | SKU       | Mounting        | Wattage | Voltage | Dimensions              | Finish | CCT   | Beam Angle | Material  | Driver | IP Rating | Luminous Flux | CRI  | Colour Deviation | Lifetime     |
|---|-----------|-----------------|---------|---------|-------------------------|--------|-------|------------|-----------|--------|-----------|---------------|------|------------------|--------------|
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 3000K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 3000K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 4000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 4000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 4000K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 4000K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 5000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 5000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 5000K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 5000K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 2700K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 2700K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |



| Image   | SKU       | Mounting        | Wattage | Voltage | Dimensions              | Finish | CCT   | Beam Angle | Material  | Driver | IP Rating | Luminous Flux | CRI  | Colour Deviation | Lifetime     |
|---|-----------|-----------------|---------|---------|-------------------------|--------|-------|------------|-----------|--------|-----------|---------------|------|------------------|--------------|
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 2700K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 2700K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 3000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 3000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|    | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 3000K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 3000K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 4000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 4000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 4000K | 36°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 4000K | 60°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 5000K | 15°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |
|  | SAI.WW106 | Track 3-Circuit | 12W     | 240V    | (D) Ø65mm<br>x (L) 64mm | White  | 5000K | 24°        | Aluminium | Remote | IP20      | 1050lm        | >92+ | <2 SDCM          | 50,000 hours |



Image

SKU Mounting Wattage Voltage Dimensions Finish CCT Beam Angle Material Driver IP Rating Luminous Flux CRI Colour Deviation Lifetime



SAI.WW106 Track 3-Circuit 12W 240V (D) Ø65mm x (L) 64mm White 5000K 36° Aluminium Remote IP20 1050lm >92+ <2 SDCM 50,000 hours



SAI.WW106 Track 3-Circuit 12W 240V (D) Ø65mm x (L) 64mm White 5000K 60° Aluminium Remote IP20 1050lm >92+ <2 SDCM 50,000 hours