



Mounting	Inground
Wattage	22W, 44W
Voltage	DC24V
Dimensions	(W) 68mm x (H) 31.5mm x (L) 1025mm, (W) 68mm x (H) 31.5mm x (L) 549mm
Finish	Stainless Steel
CCT	3000K, 4000K
Beam Angle	20°, 45°, 45°/35°
Material	Aluminium, Stainless Steel
Driver	Remote
IP Rating	IP67
IK Rating	IK07
Luminous Flux	1000lm, 2100lm
CRI	>83+
Colour Deviation	<3 SDCM
Lifetime	50,000 hours
Accessories	Honeycomb Lense
Control Gear	1-10V, DALI, Non-dimmable
Warranty	5 years
Luminaires Type	Outdoor
Luminous Flux lm	2001-2500lm, 501-1000lm

Control Gear

Accessories
Honeycomb Lense

SMOO.RLWW68							
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR	

VARIATIONS




Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SMOO.RLWW68	Inground	22W	DC24V	(W) 68mm x (H) 31.5mm x (L) 1025mm	Stainless Steel	3000K	20°	Aluminium	IP67	IK07	1000lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	22W	DC24V	(W) 68mm x (H) 31.5mm x (L) 1025mm	Stainless Steel	3000K	20°	Aluminium	IP67	IK07	2100lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	22W	DC24V	(W) 68mm x (H) 31.5mm x (L) 1025mm	Stainless Steel	3000K	20°	Stainless Steel	IP67	IK07	1000lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor	Remote

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	3000K	20°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	3000K	45°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	3000K	45°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	3000K	45°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	3000K	45°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	3000K	45°/35°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	3000K	45°/35°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	3000K	45°/35°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	3000K	45°/35°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	4000K	20°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	4000K	20°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	4000K	20°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	4000K	20°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.5mm x (L) 1025mm	Stainless Steel	4000K	45°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 1025mm	Stainless Steel	4000K	45°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 1025mm	Stainless Steel	4000K	45°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 1025mm	Stainless Steel	4000K	45°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 1025mm	Stainless Steel	4000K	45°/35°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 1025mm	Stainless Steel	4000K	45°/35°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 1025mm	Stainless Steel	4000K	45°/35°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 1025mm	Stainless Steel	4000K	45°/35°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	20°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	20°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	20°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	20°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°/35°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°/35°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°/35°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°/35°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	20°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	20°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	20°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	20°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	45°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	45°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	45°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	45°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	45°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	45°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	45°/35°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SMOO.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.15mm x (L) 349mm	Stainless Steel	4000K	45°/35°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.15mm x (L) 349mm	Stainless Steel	4000K	45°/35°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	22W	DC24V	(W) 68mm (H) 8.15mm x (L) 349mm	Stainless Steel	4000K	45°/35°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	20°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	20°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	20°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	20°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	45°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	45°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	45°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	45°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	45°/35°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	45°/35°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	45°/35°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	3000K	45°/35°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	20°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	20°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	20°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	20°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	45°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	45°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	45°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	45°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	45°/35°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	45°/35°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	45°/35°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 1025mm	Stainless Steel	4000K	45°/35°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.15mm x (L) 549mm	Stainless Steel	3000K	20°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	20°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	20°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	20°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°/35°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°/35°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°/35°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	3000K	45°/35°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	20°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	20°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.4mm x (L) 549mm	Stainless Steel	4000K	20°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.1mm x (L) 549mm	Stainless Steel	4000K	20°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.1mm x (L) 549mm	Stainless Steel	4000K	45°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.1mm x (L) 549mm	Stainless Steel	4000K	45°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.1mm x (L) 549mm	Stainless Steel	4000K	45°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.1mm x (L) 549mm	Stainless Steel	4000K	45°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.1mm x (L) 549mm	Stainless Steel	4000K	45°/35°	Aluminium	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.1mm x (L) 549mm	Stainless Steel	4000K	45°/35°	Aluminium	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.1mm x (L) 549mm	Stainless Steel	4000K	45°/35°	Stainless Steel	IP67	IK07	1000lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SM00.RLWW68	Inground	44W	DC24V	(W) 68mm (H) 8.1mm x (L) 549mm	Stainless Steel	4000K	45°/35°	Stainless Steel	IP67	IK07	2100lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote