

LS

SMOO.WW25.....

SMOO WALL WASHER 25

Luminaires Type, Outdoor



Mounting	Surface
Wattage	12W, 24W
Voltage	DC24V
Dimensions	(W) 25mm x (H) 25.6mm x (L) 1000mm, (W) 25mm x (H) 25.6mm x (L) 500mm
Finish	Anodized Aluminium
CCT	3000K, 4000K
Beam Angle	10°/33°, 30°
Material	Glass & Aluminium
Driver	Remote
IP Rating	IP66
IK Rating	IK03
Luminous Flux	1500lm, 800lm
CRI	>83+
Colour Deviation	<3 SDCM
Lifetime	50,000 hours
Accessories	Bevel Cut Anti-Glare, Reflector
Control Gear	1-10V, DALI, Non-dimmable
Warranty	5 years
Luminaires Type	Outdoor
Luminous Flux lm	1001-1500lm, 501-1000lm

Control Gear

Accessories
Bevel Cut Anti-Glare, Reflector

SMOO.WW25						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS













Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SMOO.WW25	Surface	12W	DC24V	(W) 25mm x (H) 25.6mm x (L) 1000mm	Anodized Aluminium	3000K	10°/33°	Glass & Aluminium	Remote	IP66	IK03	800lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SMOO.WW25	Surface	12W	DC24V	(W) 25mm x (H) 25.6mm x (L) 500mm	Anodized Aluminium	3000K	30°	Glass & Aluminium	Remote	IP66	IK03	800lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SMOO.WW25	Surface	12W	DC24V	(W) 25mm x (H) 25.6mm x (L) 1000mm	Anodized Aluminium	4000K	10°/33°	Glass & Aluminium	Remote	IP66	IK03	800lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SM00.WW25	Surface	12W	DC24V	(W) 25mm (H) 25.8mm x (L) 1000mm	Anodized Aluminium	4000K	30°	Glass & Aluminium	Remote	IP66	IK03	800lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	12W	DC24V	(W) 25mm (H) 25.8mm x (L) 500mm	Anodized Aluminium	3000K	10°/33°	Glass & Aluminium	Remote	IP66	IK03	800lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	12W	DC24V	(W) 25mm (H) 25.8mm x (L) 500mm	Anodized Aluminium	3000K	30°	Glass & Aluminium	Remote	IP66	IK03	800lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	12W	DC24V	(W) 25mm (H) 25.8mm x (L) 500mm	Anodized Aluminium	4000K	10°/33°	Glass & Aluminium	Remote	IP66	IK03	800lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	12W	DC24V	(W) 25mm (H) 25.8mm x (L) 500mm	Anodized Aluminium	4000K	30°	Glass & Aluminium	Remote	IP66	IK03	800lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	24W	DC24V	(W) 25mm (H) 25.8mm x (L) 1000mm	Anodized Aluminium	3000K	10°/33°	Glass & Aluminium	Remote	IP66	IK03	1500lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	24W	DC24V	(W) 25mm (H) 25.8mm x (L) 1000mm	Anodized Aluminium	3000K	30°	Glass & Aluminium	Remote	IP66	IK03	1500lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	24W	DC24V	(W) 25mm (H) 25.8mm x (L) 1000mm	Anodized Aluminium	4000K	10°/33°	Glass & Aluminium	Remote	IP66	IK03	1500lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	24W	DC24V	(W) 25mm (H) 25.8mm x (L) 1000mm	Anodized Aluminium	4000K	30°	Glass & Aluminium	Remote	IP66	IK03	1500lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	24W	DC24V	(W) 25mm (H) 25.8mm x (L) 500mm	Anodized Aluminium	3000K	10°/33°	Glass & Aluminium	Remote	IP66	IK03	1500lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	24W	DC24V	(W) 25mm (H) 25.8mm x (L) 500mm	Anodized Aluminium	3000K	30°	Glass & Aluminium	Remote	IP66	IK03	1500lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	24W	DC24V	(W) 25mm (H) 25.8mm x (L) 500mm	Anodized Aluminium	4000K	10°/33°	Glass & Aluminium	Remote	IP66	IK03	1500lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor
	SM00.WW25	Surface	24W	DC24V	(W) 25mm (H) 25.8mm x (L) 500mm	Anodized Aluminium	4000K	30°	Glass & Aluminium	Remote	IP66	IK03	1500lm	>83+	<3 SDCM	50,000 hours	5 years	Outdoor