



Mounting	<u>Surface</u>
Wattage	<u>24W, 48W</u>
Voltage	<u>DC24V</u>
Dimensions	<u>(W) 60mm x (H) 38mm</u>
Length	<u>1000mm, 500mm</u>
Finish	<u>Anodized Aluminium</u>
CCT	<u>3000K, 4000K</u>
Beam Angle	<u>15°, 15°/30°</u>
Material	<u>Glass & Aluminium</u>
Driver	<u>Remote</u>
IP Rating	<u>IP66</u>
IK Rating	<u>IK05</u>
Luminous Flux	<u>1700lm, 3500lm</u>
CRI	<u>>83+</u>
Colour Deviation	<u><3 SDCM</u>
Lifetime	<u>50,000 hours</u>
Accessories	<u>Bevel Cut Anti-Glare, Reflector</u>
Control Gear	<u>1-10V, DALI, Non-dimmable</u>
Warranty	<u>5 years</u>
Luminaires Type	<u>Outdoor</u>
Luminous Flux lm	<u>1501-2000lm, 3001+lm</u>

Control Gear

Accessories
Bevel Cut Anti-Glare, Reflector

SMOO.WW60						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Length	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SMOO.WW60	Surface	24W	DC24V	(W) 60mm x (H) 38mm	500mm	Anodized Aluminium	3000K	15°	Glass & Aluminium	IP66	IK05	1700lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	24W	DC24V	(W) 60mm x (H) 38mm	500mm	Anodized Aluminium	3000K	15°/30°	Glass & Aluminium	IP66	IK05	1700lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	24W	DC24V	(W) 60mm x (H) 38mm	500mm	Anodized Aluminium	4000K	15°	Glass & Aluminium	IP66	IK05	1700lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Length	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SMOO.WW60	Surface	24W	DC24V	(W) 60mm (H) 38mm	500mm	Anodized Aluminium	3000K	15°	Glass & Aluminium	IP66	IK05	1700lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	24W	DC24V	(W) 60mm (H) 38mm	500mm	Anodized Aluminium	3000K	15°/30°	Glass & Aluminium	IP66	IK05	1700lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	24W	DC24V	(W) 60mm (H) 38mm	500mm	Anodized Aluminium	4000K	15°/30°	Glass & Aluminium	IP66	IK05	1700lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	24W	DC24V	(W) 60mm (H) 38mm	500mm	Anodized Aluminium	4000K	15°	Glass & Aluminium	IP66	IK05	1700lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	48W	DC24V	(W) 60mm (H) 38mm	1000mm	Anodized Aluminium	3000K	15°	Glass & Aluminium	IP66	IK05	3500lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	24W	DC24V	(W) 60mm (H) 38mm	500mm	Anodized Aluminium	4000K	15°/30°	Glass & Aluminium	IP66	IK05	1700lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	48W	DC24V	(W) 60mm (H) 38mm	1000mm	Anodized Aluminium	4000K	15°/30°	Glass & Aluminium	IP66	IK05	3500lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	48W	DC24V	(W) 60mm (H) 38mm	1000mm	Anodized Aluminium	3000K	15°/30°	Glass & Aluminium	IP66	IK05	3500lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	48W	DC24V	(W) 60mm (H) 38mm	Any Length	Anodized Aluminium	4000K	15°/30°	Glass & Aluminium	IP66	IK05	3500lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	48W	DC24V	(W) 60mm (H) 38mm	1000mm	Anodized Aluminium	4000K	15°	Glass & Aluminium	IP66	IK05	3500lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	48W	DC24V	(W) 60mm (H) 38mm	1000mm	Anodized Aluminium	3000K	15°	Glass & Aluminium	IP66	IK05	3500lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	48W	DC24V	(W) 60mm (H) 38mm	1000mm	Anodized Aluminium	3000K	15°/30°	Glass & Aluminium	IP66	IK05	3500lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote
	SMOO.WW60	Surface	48W	DC24V	(W) 60mm (H) 38mm	1000mm	Anodized Aluminium	4000K	15°	Glass & Aluminium	IP66	IK05	3500lm	>83+	≤3 SDCM	50,000 hours	5 years	Outdoor	Remote