




Mounting	Recessed
Wattage	1W
Voltage	DC48V
Dimensions	(D) Ø20mm x (H) 60mm
Cut Out Dimensions	(D) Ø17mm
Finish	Black, White
CCT	2700K, 3000K, 3500K, 4000K
Beam Angle	15°, 24°
Material	Aluminium
Driver	Remote
IP Rating	IP20
UGR	<19
Luminous Flux	26lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Control Gear	1-10V, DALI, Non-dimmable
Warranty	5 years
Luminaires Type	Recessed
Luminous Flux lm	1-500lm

Control Gear

Accessories

SPEK.D20						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	Black	2700K	15°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	Black	2700K	24°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	Black	3000K	15°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Cut Out Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	UGR	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	Black	3000K	24°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	Black	3500K	15°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	Black	3500K	24°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	Black	4000K	15°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	Black	4000K	24°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	White	2700K	15°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	White	2700K	24°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	White	3000K	15°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	White	3000K	24°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	White	3500K	15°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	White	3500K	24°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	White	4000K	15°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed
	SPEK.D20	Recessed	1W	DC48V	(D) Ø20mm x (H) 60mm	(D) Ø17mm	White	4000K	24°	Aluminium	Remote	IP20	<19	26lm	>92+	<2 SDCM	50,000 hours	5 years	Recessed