



VERVE ADJUSTABLE SPOT 100

Luminaires Type, Outdoor



Mounting	Spike, Surface, Tree Mounted, Wall
Voltage	DC24V
Wattage	18W
Dimensions	(D) Ø94mm x (L) 169mm x (H) 536mm
Finish	Black
CCT	3000K, 4000K
Beam Angle	15°60
Material	Aluminium
IP Rating	IP66
IK Rating	IK05
Luminous Flux	1669lm
CRI	>90+
Colour Deviation	<3 SDCM
Lifetime	50,000 hours
Control Gear	1-10V, DALI, Non-dimmable
Accessories	Garden Spike, Tree Mount Strap, Spiked Extension Post 1000mm, Spiked Extension Post 300mm, Spiked Extension Post 500mm, Spiked Extension Post 800mm, Surface Extension Post 1000mm, Surface Extension Post 300mm, Surface Extension Post 500mm, Surface Extension Post 800mm, Surface Mount, Wall Mount
Driver	Remote
Warranty	5 years
Luminaires Type	Outdoor
Luminous Flux lm	1-500lm

Control Gear

Accessories

Garden Spike, Tree Mount Strap, Spiked Extension Post 1000mm, Spiked Extension Post 300mm, Spiked Extension Post 500mm, Spiked Extension Post 800mm, Surface Extension Post 1000mm, Surface Extension Post 300mm, Surface Extension Post 500mm, Surface Extension Post 800mm, Surface Mount, Wall Mount

VERVE.SAP100						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Voltage	Wattage	Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Driver	Warranty	Luminaires Type
	VERVE.SAP100 Spike	Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	3000K	15°60	Aluminium	IP66	IK05	1669lm	>90+	<3 SDCM	50,000 hours	Remote	5 years	Outdoor
	VERVE.SAP100 Spike	Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	3000K	15°60	Aluminium	IP66	IK05	1669lm	>90+	<3 SDCM	50,000 hours	Remote	5 years	Outdoor
	VERVE.SAP100 Spike	Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	3000K	15°60	Aluminium	IP66	IK05	1669lm	>90+	<3 SDCM	50,000 hours	Remote	5 years	Outdoor





Image	SKU	Mounting	Voltage	Wattage	Dimensions	Finish	CCT	Beam Angle	Material	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Driver	Warranty	Luminaires Type
	VERVE.SAP100 Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	3000K	15°60	Aluminium	IP66	IK05	1669lm	>90+ <3 SDCM	50,000 hours	Remote	5 years	Outdoor		
	VERVE.SAP100 Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	3000K	15°60	Aluminium	IP66	IK05	1669lm	>90+ <3 SDCM	50,000 hours	Remote	5 years	Outdoor		
	VERVE.SAP100 Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	3000K	15°60	Aluminium	IP66	IK05	1669lm	>90+ <3 SDCM	50,000 hours	Remote	5 years	Outdoor		
	VERVE.SAP100 Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	4000K	15°60	Aluminium	IP66	IK05	1669lm	>90+ <3 SDCM	50,000 hours	Remote	5 years	Outdoor		
	VERVE.SAP100 Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	4000K	15°60	Aluminium	IP66	IK05	1669lm	>90+ <3 SDCM	50,000 hours	Remote	5 years	Outdoor		
	VERVE.SAP100 Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	4000K	15°60	Aluminium	IP66	IK05	1669lm	>90+ <3 SDCM	50,000 hours	Remote	5 years	Outdoor		
	VERVE.SAP100 Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	4000K	15°60	Aluminium	IP66	IK05	1669lm	>90+ <3 SDCM	50,000 hours	Remote	5 years	Outdoor		
	VERVE.SAP100 Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	4000K	15°60	Aluminium	IP66	IK05	1669lm	>90+ <3 SDCM	50,000 hours	Remote	5 years	Outdoor		
	VERVE.SAP100 Spike	DC24V	18W	(D) Ø94mm (L) 169mm x (H) 536mm	Black	4000K	15°60	Aluminium	IP66	IK05	1669lm	>90+ <3 SDCM	50,000 hours	Remote	5 years	Outdoor		