



Mounting	Spike
Wattage	20W
Voltage	DC24V
Dimensions	(D) Ø60mm x (L) 100mm x (H) 384mm
Finish	Black
CCT	3000K, 4000K
Beam Angle	10°60°, 10°, 20°30°, 25°, 50°, 56°
Material	Aluminium
Driver	Remote
IP Rating	IP66
IK Rating	IK05
Luminous Flux	1560lm
CRI	>90+
Colour Deviation	<3 SDCM
Lifetime	50,000 hours
Control Gear	1-10V, DALI, Non-dimmable
Accessories	Garden Spike, Tree Mount Strap, Spiked Extension Post 1000mm, Spiked Extension Post 300mm, Spiked Extension Post 500mm, Spiked Extension Post 800mm, Surface Extension Post 1000mm, Surface Extension Post 300mm, Surface Extension Post 500mm, Surface Extension Post 800mm, Wall Mount
Warranty	5 years
Luminaires Type	Outdoor
Luminous Flux lm	1501-2000lm

Control Gear

Accessories

Garden Spike, Tree Mount Strap, Spiked Extension Post 1000mm, Spiked Extension Post 300mm, Spiked Extension Post 500mm, Spiked Extension Post 800mm, Surface Extension Post 1000mm, Surface Extension Post 300mm, Surface Extension Post 500mm, Surface Extension Post 800mm, Wall Mount

VERVE.SP100						
PRODUCT NAME	WATTAGE	FINISH	INNER TRIM FINISH	CCT	BEAM ANGLE	CONTROL GEAR

VARIATIONS

Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm x (L) 100mm x (H) 384mm	Black	3000K	10°60°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm x (L) 100mm x (H) 384mm	Black	3000K	10°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm x (L) 100mm x (H) 384mm	Black	3000K	20°30°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor



Image	SKU	Mounting	Wattage	Voltage	Dimensions	Finish	CCT	Beam Angle	Material	Driver	IP Rating	IK Rating	Luminous Flux	CRI	Colour Deviation	Lifetime	Warranty	Luminaires Type
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm (L) 100mm x (H) 384mm	Black	3000K	25°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm (L) 100mm x (H) 384mm	Black	3000K	50°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm (L) 100mm x (H) 384mm	Black	3000K	56°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm (L) 100mm x (H) 384mm	Black	4000K	10°/60°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm (L) 100mm x (H) 384mm	Black	4000K	10°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm (L) 100mm x (H) 384mm	Black	4000K	20°/30°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm (L) 100mm x (H) 384mm	Black	4000K	25°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm (L) 100mm x (H) 384mm	Black	4000K	50°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor
	VERVE.SP100 Spike		20W	DC24V	(D) Ø60mm (L) 100mm x (H) 384mm	Black	4000K	56°	Aluminium	Remote	IP66	IK05	1560lm	>90+	<3 SDCM	50,000 hours	5 years	Outdoor