


# MINO SURFACE R65



## Specifications

Mounting	Surface Mounting
Wattage	10W
Voltage	240V
Dimensions	(D) Ø65mm x (H) 100mm
Finish	Black/White
Inner Trim Finish	Black/White/Anthracite
CCT	2700K/3000K/4000K/5000K
Beam Angle	15°/24°/36°/60°
Material	Aluminum
Driver	Inbuilt
IP Rating	IP20
UGR	
Luminous Flux	861lm
CRI	>92+
Colour Deviation	<2 SDCM
Lifetime	50,000 hours
Adjustability	

Accessories	Honeycomb Lens, Soft Lens, Diffuser Lens
Control Gear	TRIAC
Warranty	3 years

## Product Accessories

Honeycomb Lens



Soft Lens



Diffuser Lens



## Product Code

Example - MINO.SFR65.10.BLK.BLK.27.15.HCMB.TRIAC

Product	Wattage	Finish	Inner Trim	CCT	Beam Angle	Accessories	Control Gear
MINO.SFR65	10(W)	BLK (Black)	BLK (Black)	27 (00K)	15(°)	HCMB (Honeycomb Lens)	TRIAC (TRIAC)
		WHT (White)	WHT (White)	30 (00K)	24(°)	SFLS (Honeycomb Lens)	DALI (DALI)
			ATH (Anthracite)	35 (00K)	36(°)	DFLS (Diffuser Lens)	
			40 (00K)	60(°)			