


MINO SURFACE SPOTLIGHT 65



Specifications

Mounting	Surface Mounting	Accessories	Honeycomb Lens, Soft Lens, Diffuser Lens, Tube
Wattage	15W	Control Gear	TRIAC, DALI
Voltage	240V	Warranty	3 years
Dimensions	(D) Ø65mm x (L) 155mm		
Finish	Black/White		
Inner Trim Finish	Black/White/Anthracite		
CCT	2700K/3000K/4000K/5000K		
Beam Angle	36°/24°/36°/60°		
Material	Aluminum		
Driver	Inbuilt		
IP Rating	IP20		
UGR			
Luminous Flux	1207lm		
CRI	>92+		
Colour Deviation	<2 SDCM		
Lifetime	50,000 hours		
Adjustability			

Product Accessories

Honeycomb Lens



Soft Lens



Diffuser Lens



Tube



Product Code

Example - MINO.SS65.15.BLK.BLK.27.15.HCMB.TRIAC

Product	Wattage	Finish	Inner Trim	CCT	Beam Angle	Accessories	Control Gear
MINO.SS65	15(W)	BLK (Black)	BLK (Black)	27 (00K)	15(°)	HCMB (Honeycomb Lens)	TRIAC (TRIAC)
		WHT (White)	WHT (White)	30 (00K)	24(°)	SFLS (Honeycomb Lens)	DALI (DALI)
			ATH (Anthracite)	40 (00K)	36(°)	DFLS (Diffuser Lens)	
				50 (00K)	60(°)	TUBE (Tube)	