


# SNOOK SPOTLIGHT 83



## Specifications

|                   |   |
|-------------------|---|
| Mounting          | Recessed Mounting                           |
| Wattage           | 10W   |
| Voltage           | 240V  |
| Dimensions        | (D) Ø83mm x (H) 70mm<br>Cut Out - (D) Ø75mm |
| Finish            | Black/White                                 |
| Inner Trim Finish | Black/White                                 |
| CCT               | 2700K/3000K/3500K/4000K                     |
| Beam Angle        | 15°/24°/36°/60°                             |
| Material          | Aluminum                                    |
| Driver            | Remote                                      |
| IP Rating         | IP20  |
| UGR               | <19   |
| Luminous Flux     | 532lm                                       |
| CRI               | >92+  |
| Colour Deviation  | <2 SDCM                                     |
| Lifetime          | 50,000 hours                                |

|               |  |
|---------------|--|
| Adjustability |  |
| Accessories   | Honeycomb Lens, Soft Lens, Diffuser Lens |
| Control Gear  | TRIAC/DALI                               |
| Warranty      | 5 years                                  |

## Product Accessories

Honeycomb Lens



Soft Lens



Diffuser Lens



## Product Code

Example - SNOOK.S83.10.BLK.BLK.27.15.HCMB.TRIAC

| Product   | Wattage | Finish                     | Inner Trim                 | CCT  | Beam Angle               | Accessories  | Control Gear                 |
|-----------|---------|----------------------------|----------------------------|--|--------------------------|--|------------------------------|
| SNOOK.S83 | 10(W)   | BLK (Black)<br>WHT (White) | BLK (Black)<br>WHT (White) | 27 (00K)<br>30 (00K)<br>35 (00K)<br>40 (00K) | 15°<br>24°<br>36°<br>60° | HCMB (Honeycomb Lens)<br>SFLS (Honeycomb Lens)<br>DFLS (Diffuser Lens) | TRIAC (TRIAC)<br>DALI (DALI) |